



Preferred Safety Products, Inc.

Preferred for Quality and Practicality™
Select Safety Products™
Preferred by Craftsmen and Employers™

1-800-301-3188
www.preferredsafety.com

Standing Seam Horizontal Lifeline

PART NO. 340SSRC-03HLL-XXX

Features:

The only Horizontal Lifeline System designed for use on standing seam roofs.

- 340SSRC-03HLL-40C - 40' kit includes two 340SSRC-03 Standing Seam Roof Clamps, 40' cable assembly, two carabineers, one inline shock absorber and all the hardware needed to install this system.
- 340SSRC-03HLL-60C - 60' kit includes three 340SSRC-03 Standing Seam Roof Clamps, 60' cable assembly, three carabineers, one inline shock absorber and all the hardware needed to install this system
- 340SSRC-03HLL-25R - 25' kit includes two 340SSRC-03 Standing Seam Roof Clamps, 25' Pre-engineered life line with rope tensioner, five carabineers, two finished ends with thimble eyes and a nylon inline shock absorber.
- 340SSRC-03HLL-50R - 50' kit includes three 340SSRC-03 Standing Seam Roof Clamps, 50' Pre-engineered life line with rope tensioner, six carabineers, two finished ends with thimble eyes and a nylon inline shock absorber.

Previous

60' CABLE SYSTEM

340SSRC-03HLL-60C



Product Specs:

- Comes with instructions, sketches, warnings and certificate of compliance
- Information allows employer's qualified person's to layout, train and then install, maintain, move and oversee users on a horizontal lifeline
- Pre-engineered – complies with USACE and all OSHA requirements, subject to instructions and proper installation
- Galvanized cable with one thimble-swaged eye for vertical or horizontal lifelines
- Cable includes three drop forged cable clips, three 1/2" safety shackles, and one thimble
- Kits available in 30, 40 and 60 foot systems adjustable down to 5'
- Lightweight, reusable, easy to use
- Cable system is durable, all steel construction with zinc electroplate finish, stainless steel or galvanized parts weather resistant - long life
- Unique, patented, reversible design of seam clamp allows for seams up to 1" wide
- MR-24, VSR or similar profiles can be covered with one clamp *NOTE Use on clips anywhere on the completely seamed and attached roof sections, not closer than 4 ft. from the unfinished edge
- Cable system comes standard with a stainless steel inline shock absorber suitable for longer term out door installation
- Optional nylon inline shock absorber available (lower cost, not suited for long term outdoor installations)

Note and Warning:

Preferred Safety reserves the right to change and improve specifications design configurations, components and details at any time without notice. Check with Preferred Safety for any newer versions of products or instructions or warnings during the life of your product. The product is developed in accordance with OSHA/ANSI standards in effect at the time of manufacturing. Users should remain aware of any changes in safety and health laws or standards in the jurisdiction in which the user is operating and using Preferred Safety products. * Butler Building Co. roof seam models used as examples. Paten Pending

Copyright ©2011 - Preferred Safety Products, Inc. All rights reserved. No copying or distribution of these materials is allowed for any purpose except for sales and management uses of our customers on jobs using the system described herein.