

# 85W-140

## TECHNICAL DATA SHEET MOLY GEAR LUBRICANT

**SWACO Moly Gear Lubricant** is specially designed for enclosed gear boxes. Inhibited with a synthetic thickener, it has excellent thermal stability and resistance to oxidation. It offers superb corrosion protection.

### FEATURES:

Withstands pressures up to 100,000 PSI.  
Fluid film does not "drain off" parts  
Reduces frictional wear  
Multi-Viscosity  
Plates itself to metal surfaces

### BENEFITS:

Peak power demand is lowered  
Reduces inventory of many single weight oils  
Reduces parts replacement--heals wear scars  
Cooler gear box temperatures

### Typical Specifications

Appearance	Opaque
Color	Black
Odor	Sulfur
Viscosity @ 40 C, cST	372
Viscosity @ 100 C, cST	27.74
Viscosity Index (min)	101
Pour Point	10 F
Flash Point, COC	495 F
Gravity degrees API	.8944

**THIS HEAVY DUTY OIL IS SUITABLE FOR USE IN THE GEAR BOXES OF  
AUTOMATIC PIN SETTERS.  
IT IS LEAK RESISTANT AND CAN PROVIDE LIMITED SEALING OF  
DAMAGED SEALS/GASKETS.**

Sold by Dri-Slide North America—1452 Delashmut Avenue—Columbus, Ohio 43212  
Website: [www.russack.com](http://www.russack.com) Tel. #1-800-231-6901 or (614) 291-6929  
Email: [russack@netwalk.com](mailto:russack@netwalk.com)