



ROBOTIC GREASE LG-01-02

TECHNICAL DATA AND TYPICAL CHARACTERISTICS



Appearance	Smooth & Tacky Grease*
Color	Blue -Green
Odor	Active Chemical Odor
NLGI Grade	#2
Base Oil Viscosity	110cSt @ 104°F (40°C)
Dropping Point	470°F (243°C)
Rust Test (ASTM D-1743)	Pass
Unworked Penetration	195
Worked Penetration	265
Copper Corrosion (FTM-5309)	Pass
Temperature Range	0°F to 347°F (-18°C to 175°C)

FEATURES

“Tackiness” Additive
Synthetic Thickener
Compatibility

BENEFITS

Stays Put
Ashless
Can be used to replace sodium & lithium

MEETS GMF ROBOTICS LG-01-02

SPECIFICATION

<u>PACKAGE</u>	<u>PRODUCT #</u>	<u>CASE PACK</u>	<u>SHIPPING WEIGHT</u>
14.5 oz. cart.	DSL330	6	7 lbs.
35 lb pail	DSL335	1	35 lbs.
100 lb keg	DSL336	1	100 lbs.
400lb keg	DSL337	1	400 lbs.

Sold by Dri-Slide North America – 1452 Delashmut Avenue – Columbus, Ohio 43212
 Website: www.russack.com Tel. #1-800-231-6901 Fax #1-800-600-0855 or (614)291-6920
 Email: drislide@russack.com