



P-116 CONVEYOR CHAIN LUBRICANT

TECHNICAL DATA AND TYPICAL CHARACTERISTICS



Appearance	Liquid
Odor	Mild petroleum
Color	Black
Specific gravity	.83
Viscosity	Light Penetrating Liquid
Flash point (T.C.C.)	250°F
% Non-volatile	22
% Volatile	78
Pour Point	Less than - 40°F
Low temperature range	- 20°F
Peak temperature range	750°F
Initial Boiling Point	More than 300°F
Weight	6.8 Lbs/Gal.
Coverage	Approx. 800 Sq Ft./Gal.
Surface Tension	27 dynes/cm @ 70°F
Electrical Conductivity	N/A
Solvent KB Value	26
Corrosion Protection ASTM (D-1748)	Excellent

FEATURES

- HIGHER FLASH POINT
- CONTAINS MoS2
- NON-SETTLING MoS2
- CONTAINS CORROSION INHIBITORS

BENEFITS

- FEWER EPA MONITORED EMISSIONS. ABLE TO USE IN HIGHER TEMPERATURE ENVIRONMENT
- HIGH PRESSURE LOAD DOES NOT ATTRACT DIRT & CAN BE USED IN HIGH TEMP. ENVIRONMENT
- WORKS IN ALL CENTRAL LUBRICATING EQUIPMENT
- PREVENTS RUST ON METAL AND PROVIDES EXCELLENT ACID FUM PROTECTION

<u>PACKAGE</u>	<u>PRODUCT #</u>	<u>CASE PACK</u>	<u>SHIPPING WEIGHT</u>
5 gal. pail	DSL505	1	40 lbs
16 gal. drum	DSL515	1	125 lbs
55 gal. drum	DSL555	1	415 lbs

Sold by Dri-Slide North America – 1452 Delashmut Avenue – Columbus, Ohio 43212

Website: www.russack.com Tel. #1-800-231-6901 Fax #1-800-600-0855 or (614)291-6929