



39362 SEM SOAP

TECHNICAL DATA SHEET

Description

39362 SEM SOAP is specifically designed as a first step cleaner for all repair and refinishing procedures. **39362** gravitates into the pores of the substrate and floats contaminants to the surface. **39362** also contains a slight abrasive to open the substrate for greater adhesion.

Features

- Removes wax, grease, road film, tar, etc.
- Great prep cleaner for numerous substrates
- Ensures proper cleaning for trouble-free repairs
- VOC compliant and environmentally safe
- Emulsifies contaminants for easy disposal
- Easy to use one step application
- Great for cleaning chrome, rubber and white wall tires

Typical Properties

Container	15 oz bottle
Color	Blue
Form	Gel / Liquid
VOC	.21 #/gl (25.3 g/l)

Handling and Application

APPLICATION: **39362** removes water based contaminants and should be the first step when preparing interior substrates for repair or refinishing.



1. Dampen applicator pad, such as a gray scuff pad, and apply a small amount of **39362**.
2. Scrub panel thoroughly until surface is clean and finish is dull.
3. Rinse with water. If contamination still exists after the cleaning process, water will bead on the surface. Repeat the cleaning process until beading no longer occurs. **NOTE:** When cleaning leather, do not rinse with water. Instead, wipe the **39362** with a clean, damp towel to remove all residue.
4. Blow dry and repair or refinish according to SEM **RAP-1, Refinishing Automotive Interior and Exterior Flexible and Rigid Substrates**.

NOTE: **39362** should not be used as car wash soap.

STORAGE:



39362 SEM SOAP should be stored in a cool dry place with adequate ventilation away from heat, sparks and flames. Keep from freezing. The shelf life for **39362** is 5 years when stored under normal conditions.

TECHNICAL CONSULTATION SERVICE

Our Technical Staff is ready to assist you with any questions. You are invited to take advantage of our extensive experience, laboratory services and trained field service representatives. Call (800) 831-1122 for answers to your questions. Hours of operation are Monday through Thursday 8:00 am until 5:00 pm EST and on Friday 8:00 am until 4:30 pm EST.

DISCLAIMER: The information supplied in this document is for guidance only and should not be construed as a warranty. All implied warranties are expressly disclaimed. All users of the materials are responsible for assuring that it is suitable for their needs, environment and use. All data subject to change as SEM deems appropriate.

Users should review the Material Safety Data Sheet (MSDS) and product label for the material to determine possible health hazards, appropriate engineering controls and precautions to be observed in using the material. Copies of the MSDS and product label are available upon request.