

CP 60

Razor Edge
Painter's Tape

Shurtape®

TECHNICAL DATA

TYPICAL APPLICATIONS

- > Designed to create painted patterns on walls, such as stripes, diamonds and other creative designs
- > Perfect for striping

ADVANTAGES AND BENEFITS

- > Leaves the sharpest lines possible
- > Clean removal for up to 60 days
- > Low tack for delicate surfaces
- > Special paper backing reduces bleed-through

CONSTRUCTION


Overall Grade/Function: 60 Day Painter's Tape

Backing: Smooth Paper

Adhesive: Acrylic



COLOR(S)



Gold (GOLD)

STANDARD WIDTH(S)

24mm 48mm

STANDARD LENGTH(S)

55m

Contact your Shurtape sales representative for other available sizes.

PHYSICAL PROPERTIES

	STANDARD	METRIC
Tensile Strength	23 lbs/in width	40.3 N/10 mm
Adhesion to Stainless Steel	15 oz/in width	1.60 N/10 mm
Thickness	3.8 mils	0.10 mm
Elongation	4 %	4 %

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC. Quality Assurance and Technical Service Departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

APPLICABLE SPECIFICATIONS

ASTM D6123/D6123M-97

STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.