



40903 1K HS CLEAR

TECHNICAL DATA SHEET

Description

40903 1K HS CLEAR is an aerosol packaged product designed as a quick alternative to mixing typical automotive clearcoats. It is perfect for small accessories, door jambs, and when cutting in new parts. The combination of spray tip and formulation delivers professional results. **40903** lays down flat and dries quickly saving valuable time.

Features

- Convenient aerosol – no mixing
- UV resistant – good color holdout
- Quick drying – increased production
- High gloss – excellent appearance
- Good film build – added durability
- Lays flat – professional results

Typical Properties

Container:	20 oz. aerosol
MIR:	0.9
VOC Europe:	567 g/l (4.72 lb/gal)

Handling and Application

MIXING: Shake well before using.



APPLICATION: Allow basecoat to flash according to manufacturer's instructions.



Coats: 2 full coats or 3 medium coats
 Distance: 6-8"
 Flash time: 3-5 minutes between coats

Allow **40903** to dry for at least 1 hour before handling.

IMPORTANT: If too much **40903** is applied or it is applied before the basecoat has flashed off properly, re-wetting of the basecoat could occur.

NOTE: If clogging develops, remove spray button with a twisting motion and clean with material compliant with VOC regulations in your area. Do not stick pin or other object into can. Gently replace spray button with top of can and spray button pointed away from you.

NOTE: After each use, turn can upside down and spray several seconds to clear spray tip.

STORAGE:



40903 1K HS CLEAR should be stored in a cool dry place with adequate ventilation away from heat, sparks and flames. The shelf life for **40903** is 5 years when stored under normal conditions.

TECHNICAL CONSULTATION SERVICE

Our Technical Staff is ready to assist you with any questions. You are invited to take advantage of our extensive experience, laboratory services and trained field service representatives. Call (800) 831-1122 for answers to your questions. Hours of operation are Monday through Thursday 8:00 am until 5:00 pm EST and on Friday 8:00 am until 4:30 pm EST.

DISCLAIMER: The information supplied in this document is for guidance only and should not be construed as a warranty. All implied warranties are expressly disclaimed. All users of the materials are responsible for assuring that it is suitable for their needs, environment and use. All data subject to change as SEM deems appropriate.

Users should review the Material Safety Data Sheet (MSDS) and product label for the material to determine possible health hazards, appropriate engineering controls and precautions to be observed in using the material. Copies of the MSDS and product label are available upon request.

SEM Products, Inc.
Rock Hill, SC 29730
Tel: 800/ 831-1122
www.semproducts.com