

Fusible Machine Appliqué: Poppy Wall Hanging

In this online video class you'll learn:

- How to select the perfect fabrics from your scrap stash
- The advantages of batik fabrics
- How to properly arrange and layer pieces
- Successful fusing tips and tricks
- Raw-edge appliqué and tips for success
- Machine appliqué tips with your sewing machine

QAV01 Fusible Machine Appliqué: Poppy Wall Hanging This exclusive quilt project is included as part of the class curriculum



Heart Pocket Scissors Keeper

By Mary Ayres

Both functional and very pretty, this accessory is a perfect gift for even your non-sewing friends. All scissors need a known place to be found.

Project Specifications

Skill Level: Beginner

Scissors Pocket Size: Approximately 5\%" x 9\%"

Materials

- Scraps of off-white faille, taffeta or other shiny fabric
- Scraps of unbleached muslin for backing
- Off-white doily scrap 6" x 7"
- Thin batting 6" x 10"
- 1 yard off-white piping
- 6" length of off-white ½"-wide satin ribbon
- Basic sewing supplies and tools

Instructions

Step 1. Cut fabrics, batting and lace as directed on pattern.

Step 2. Place lace half heart on top of shiny half heart. Align raw edges of off-white piping with straight raw edges of lace/shiny half heart. Sew with ¼" seam. Place muslin half heart on top of all layers, aligning straight edges. Sew on previous sewing line. Turn right side out, with shiny fabric layered between lace and muslin.

Step 3. Baste wrong side of whole heart to batting. Place muslin side of assembled half heart facing fabric side of whole heart. Starting at lower edge, sew piping around entire perimeter, ending and overlapping at lower edge. Clip seam at cleft of heart as you sew, for a smooth turn.

Step 4. Align raw ends of off-white ¼" ribbon with raw edges of top of heart, each end 1" from heart cleft. Baste in place.

Step 5. Place whole muslin heart on top of all layers. Sew around perimeter, leaving 3" opening for turning.





