

## SIMPLE, LIGHTWEIGHT, HIGH STRENGTH.



- The Tie-Off Adaptor range of anchor straps with interlocking rings can be used almost anywhere an anchorage point is needed.
- Available in a variety of lengths to suit various work applications.
- Lightweight and high strength rated to 22.2kN for personal use.
- Accommodates a wide variety of different sized structures.
- Pass through design - interlocking rings make attaching to an anchorage quick and easy.
- Coated steel hardware for corrosion resistance and strength.
- Extra heavy duty - wide integral wear pad provides abrasion resistance and extends product life.
- Easy to install and use.
- Anti roll-out design - designed to minimise the risk of roll-out when connecting the large fall arrest rated D-ring to a DBI-SALA lanyard or SRL with a 9502116 model hook.
- i-Safe™ enabled - i-Safe™ is built into every Tie-Off Adaptor to track inspections, control inventory and manage information.
- Meets or exceeds all applicable industry standards.

# TIE-OFF ADAPTOR ANCHOR STRAP



**Anchor Straps** DBI-SALA's tie-off adaptor range of interlocking anchor straps are designed to be used as an anchorage connector for fall arrest, restraint, work positioning, suspension, or rescue systems. They provide a portable fall arrest rated anchorage device that can be used almost anywhere an anchor point is needed.

**E849 Series** DBI-SALA's E849 series anchor straps are durable, lightweight, portable and easy to use. They consist of a silver D-ring on one end that passes through a larger gold D-ring fitted on the other end (interlocking rings). The strap then chokes down to become an anchor point. They are available in a variety of lengths to suit various work situations.

## Versatile Anchorage Connectors

No matter what you are connecting to, DBI-SALA has an anchorage product to help you get the job done and keep you safe in case of a fall.



*Typical overhead application shown.*

## Tie-Off Adaptor Models:

- E849-005:** 0.5m Interlocking Anchor Strap
- E849-008:** 0.8m Interlocking Anchor Strap
- E849-010:** 1.0m Interlocking Anchor Strap
- E849-012:** 1.2m Interlocking Anchor Strap
- E849-015:** 1.5m Interlocking Anchor Strap
- E849-020:** 2.0m Interlocking Anchor Strap

## Specifications:

**Colour:** Blue & Yellow. **Webbing:** Polyester, resistant to UV and common organic solvents (if in doubt contact manufacturer); Width - Anchor Strap 45mm, Wear Pad 75mm. **Hardware:** Large gold D-ring - Fall arrest rated, drop forged alloy steel, minimum tensile strength 22.2kN, internal diameter width - 79mm; Silver D-ring - Fall arrest rated, drop forged alloy steel, minimum tensile strength 22kN, internal diameter width - 54mm. **Weight (approx):** E849-005 - 430g, E849-008 - 500g, E849-010 - 550g, E849-012 - 600g, E849-015 - 650g, E849-020 - 800g. **Capacity:** Rated to 22.2kN. **Compatibility:** DBI-SALA anchor straps are designed for use with DBI-SALA approved components or systems, or as recommended by a competent person. **Standards:** AS/NZS 1891.1 **Country of Origin:** Australia. **Special Instructions/Conditions of Use:** Reading user instruction manual prior to use is essential. Always ensure maximum fall arrest distance is less than 2m and an energy absorbing lanyard is used in the assembly.

## Capital Safety:

Australia: 1800 245 002 New Zealand: 0800-212 505 Asia: +852 2992 0381  
USA: 800-328-6146 Canada: 800-387-7484 Northern Europe: +44 (0) 1928 57 1324  
Europe, Middle East & Africa: +33 (0) 497 10 00 10 Or visit: [WWW.CAPITALSAFETY.COM.AU](http://WWW.CAPITALSAFETY.COM.AU)

