

**Description**

Reprotec Toolclean is an equipment cleaner suitable for the removal of uncured Epoxy, Polyester and Polyurethane resins. It has a low evaporation rate, mild odour and low toxicity, making it much more user friendly than other commonly used solvents. Reprotec Toolclean is also largely biodegradable and photochemically non-reactive, and therefore more acceptable from an environmental point of view.

**Typical Uses**

Equipment cleaning.  
Uncured resin removal.  
Paint and Graffiti removal.

**Advantages**

- Low Hazard
- Low evaporation rate
- Excellent solvency powers
- 80% Biodegradable

**Typical Properties**

Appearance: clear, colourless liquid  
Odour: mild, sweet  
Flash Point: 31°C  
Vapour Pressure: 10mm Hg @ 20°C  
Specific Gravity: 0.921 @ 20°C  
Solubility in water: Soluble

**Packaging**

Reprotec Toolclean is supplied in 5ltr packs

**Storage and Shelf Life**

Store in dry conditions, out of direct sunlight, at temperatures between 10°C and 25°C.

Reprotec Toolclean has a minimum shelf life of 12 months when stored in original, unopened containers in accordance with manufacturer's instructions.

**Health and Safety**

Do not breathe vapour/spray.  
Avoid contact with skin and eyes.  
Provide adequate ventilation.

Refer to Material Safety Data Sheet for further information.

Reprotec Toolclean shall be applied strictly in accordance with the manufacturer's instructions.

For specific advice regarding any aspect of this product please consult our Technical section.