



8-Port 10/100Mbps Module TEG-S3M8TX

FEATURES

- Compliant with IEEE 802.3 10Base-T, IEEE 802.3u 100Base-TX and IEEE 802.3x Flow Control
- 8 x 10/100Mbps Auto-Negotiating and Auto-MDIX RJ-45 Ports
- Optional Modules for TEG-S3000i (Layer 2 Managed Chassis Switch)
- 5-Year Warranty

8-Port 10/100Mbps Module

TEG-S3M8TX

SPECIFICATIONS

Hardware	
Standards	<ul style="list-style-type: none">• IEEE 802.3 :10Base-T• IEEE 802.3u : 100Base-TX• IEEE 802.3x : Flow Control
Interface	<ul style="list-style-type: none">• 8 10/100Mbps Auto-MDIX Fast Ethernet RJ-45 Ports
Switch Architecture	<ul style="list-style-type: none">• Store/Forward
LED	<ul style="list-style-type: none">• Link, Activity, Full-duplex
Data Transfer Rate	<ul style="list-style-type: none">• Ethernet: 14880pps• Fast Ethernet: 148800pps
Network Cable	<ul style="list-style-type: none">• Ethernet: Cat. 3,4,5• Fast Ethernet: Cat. 5
Protocol	<ul style="list-style-type: none">• CSMA/CD
Dimensions	<ul style="list-style-type: none">• 126 x 46 x 35mm (5.0 x 1.8 x 1.4 in.)
Weight	<ul style="list-style-type: none">• 213g (7.6oz.)
Temperature	<ul style="list-style-type: none">• Operating: 0°~45°C (32°~113°F) • Storage: -10°~70°C (14°~158°F)
Humidity	<ul style="list-style-type: none">• 10%~90% (non-condensing)
Certification	<ul style="list-style-type: none">• CE, FCC



PACKAGE CONTENTS

- TEG-S3M8TX

RELATED PRODUCTS

TEG-S3000i	4-Slot Gigabit Layer 2 Managed Chassis
TEG-S3M8FX	8-Port 100Base-FX SC Type Multi-Mode Fiber Module
TEG-S3M8S15	8-Port 100Base-FX SC Type Single-Mode Fiber Module
TEG-S3M2CG	2 Gigabit Copper Port
TEG-S3M2MG	2 Mini-GBIC Slot
TEG-S3M11CF	Gigabit Copper and Fiber Combo

ORDERING INFORMATION

TRENDnet

3135 Kashiwa Street, Torrance, CA 90505 USA
Tel: 1-310-891-1100
Fax: 1-310-891-1111
Web: www.trendnet.com
Email: sales@trendnet.com

To Order Please Call:

1-888-326-6061