





3G Mobile Wireless Router TEW-655BR3G (V1.0R)

The 3G Mobile Wireless Router (model TEW-655BR3G) connects to the Internet either using a traditional hard wired connection or by cutting the cables and connecting with a compatible wireless mobile USB dongle from a 3G* Internet service provider such as AT&T™, T-Mobile™, or Verizon™**.

Designed for true portability the router has a rechargeable and replaceable 2.5 hour lithium ion battery. Compatible with USB dongles from every mobile provider, this compact router connects to the Internet anywhere there is a 3G* mobile connection.

No installation is required, simply plug the 3G* USB adapter into the router to share a single Internet connection. The latest wireless encryption protects your valuable data. Wi-Fi Protected Setup (WPS) integrates other WPS supported clients at the touch of a button. An on/off switch on the back of the devices saves battery life. For long trips, power the router with TRENDnet's Car Adapter, model TA-CC.


FEATURES •1 x 10/100Mbps LAN port

- Works with UMTS/HSPA or EV-DO mobile networks *
- UMTS/HSPA, WCDMA (HSDPA), CDMA2000 (EV-DO) & TD-SCDMA
- High-speed data rates up to 150Mbps using an IEEE 802.11n connection**
- Built-in antennas provide high-speed performance and expansive wireless coverage
- · Multiple SSID with wireless or wired/wireless clients isolation support
- Advanced Firewall protection with Network Address Translation (NAT) and Stateful Packet Inspection (SPI)
- Access restriction with Internet Access Control; URL and MAC filtering
- Built in pre-configured virtual servers and Application Level Gateway services for special Internet applications
- Universal Plug and Play (UPnP) for auto discovery and support for device configuration of Internet applications
- Easy setup via Web browser using the latest versions of Internet Explorer, FireFox, Netscape, Safari and Chrome
- One touch wireless security setup using the Wi-Fi Protected Setup (WPS) button
- Complete wireless security with WPA/WPA2, WPA-PSK/WPA2-PSK, and WEP
- · Works with Windows, Linux and Mac operating systems
- 3-year llimited warranty
- *Go to www.trendnet.com for a list of compatible 3G/4G USB adapters
- **Must have an active Internet plan with the respective third party mobile provider
- **Maximum wireless signal rates are referenced from IEEE 802.11 theoretical specifications. Actual data throughput and coverage will vary depending on interference, network traffic, building materials and other conditions.

SPECIFICATIONS

Hardware	
Standards	Wired: IEEE 802.3 (10Base-T), IEEE 802.3u (100Base-TX) Wireless: IEEE 802.11b, IEEE 802.11g, IEEE 802.11n
	• USB: USB 2.0, USB 1.1
USB WAN	1 x USB 2.0 port for 3G USB adapter (Internet)
LAN /WAN (optional)	1 x 10/100Mbps Auto-MDIX port (Internet)
WPS Button	Wi-Fi Protected Setup (WPS) with other WPS compliant devices
WAN Connection Type	Dynamic IP, Static (fixed) IP, 3G
Compatible 3G/3.5G Mobile Networks	UMTS/HSPA, WCDMA (HSDPA), CDMA2000 (EV-DO) & TD-SCDMA
Compatible Carriers in USA	AT&T, Verizon **** (need to write disclaimer)
Compatible USB Adapters	AT&T USBConnect QuickSilver
Router/ Firewall	 NAT, NAPT and SPI DoS (blocking ping, port scan, sync flood) UPnP, DMZ, Static/Dynamic Route support Static / Dynamic Route (RIP v1/v2) MAC, port range, service, domain and URL filtering (deny or allow) and ICMP blocking
Power Switch	Slide On/Off
Battery	3.7V, 1700MAh Li-ION battery (Compliant to NP120)
LED Indicator	Power, 3G, WPS, WAN, WLAN, LAN1, LAN2
Power Adapter	• 5V, 2A DC
Power Consumption	System Operation: 350mA (max) Battery Charging: 900mA (max)
Dimension (L x W x H)	• 107 x 76 x 21 mm (4.2 x 2.9 x 0.8 inches)
Weight	• 97.38g
Temperature	• Operation: 0°~ 45°C (32°F~ 113°F) • Storage: -10°~ 70°C (14°F~158°F)
Humidity	Max. 95% (non-condensing)
Certifications	• CE, FCC
Wireless	
Frequency	• 2.400 ~ 2.484GHz
Module Technique	OFDM, DSSS, BPSK, QPSK, CCK
Data Rate	802.11b: up to 11Mbps
Security	64/128-bit WEP, WPA-PSK(TKIP)/WPA2-PSK(AES)
Output Power	• 802.11b: 13dBm • 802.11g: 11dBm • 802.11n: 10dBm
Receiving Sensitivity	• 802.11b: -85dBm • 802.11g: -70dBm • 802.11n: -68dBm
Channels	• 1~ 11 (FCC), 1~13 (ETSI)

NETWORKING SOLUTIONS



PACKAGE CONTENTS

- TEW-655BR3G
- · Multi-Language Quick Installation Guide
- CD-ROM (Utility and Driver)
- Cat.5 Ethernet cable (1m / 3.2ft)
- Power adapter 5v, 2A
- Battery 3.7V, 1700mAh

RELATED PRODUCTS

TEW-649UB	Mini Wireless N Speed USB Adapter
TEW-643PI	Wireless N PCI Adapter
TEW-638APB	300Mbps Wireless N Access Point

ORDERING INFORMATION

TRENDNET

20675 Manhattan Place, Torrance, CA 90501 USA

Tel: 1-310-961-5500 Fax: 1-310-961-5511 Web: www.trendnet.com Email: sales@trendnet.com

To Order Please Call:

1-888-326-6061

