





4-Port USB KVM Switch Kit with Audio TK-409K

The 4-Port USB KVM Switch with Audio lets you manage 4 computers with just one set of keyboard, monitor, mouse, and a set of speakers/Microphone. The device comes with 4 sets of USB KVM and Audio cables, no additional equipment required. Its compact size makes it ideal for home and business environment.


- FEATURES Use one keyboard, monitor, and mouse to control two computers
 - 4-port USB KVM Switch with 1 set of Mic/Speaker port.
 - 4 sets of VGA and 4 sets of Audio & Microphone Cables
 - Supports Microsoft IntelliMouse, Optical Mouse, Logitech Net Mouse and more
 - Supports super High Video Quality, up to 2048 x 1536 VGA resolution
 - Supports Windows 98(SE)/ME/2000/XP/2003 Server, Linux, and Mac OS
 - Multi-Platform supports for PCs, Macintosh G3/G4, iMac and Mac Mini
 - · Auto-Scan & LED display for PCs monitoring
 - · Hot-Key, push button and Windows-based client switching software
 - User definable hot-key (Windows Only)
 - Plug & Play and Hot-Pluggable
 - USB Interface Power method
 - 2-Year Warranty

4-Port USB KVM Switch Kit with Audio TK-409K

SPECIFICATIONS

| Hardware | | |
|--------------------|---|--|
| Management | • 4 computers | |
| USB Interface | USB 1.1 Specifications Compliant | |
| KVM Cable | • 4 Sets of 1.2M (4ft) KVM Cables • 4 Sets of Audio/Microphone Cables (USB mini B to 3.5mm Jack) | |
| Cable Interface | KVM: To KVM: 1 x VGA/SVGA HDB 15-pin (male) To PC: 1 x USB (Type A), 1 x VGA/SVGA HDB 15-Pin (male) | |
| | Audio: To KVM: 1 x 3.5mm audio in/out jack, 1 x 3.5mm microphone in/out jack To PC: 1 x 3.5mm audio in/out jack, 1 x 3.5mm microphone in/out jack | |
| Console Connectors | • 1 x USB Keyboard (Type A) • 1 x USB Mouse (Type A) • 1 x VGA/SVGA HDB 15-pin | |
| | • 1 x 3.5mm audio in/out jack • 1 x 3.5mm microphone in/out jack | |
| Port Selection | Push Button, Hot-Key Commands, or Windows-Based Client Switching Software | |
| Auto-Scan Interval | • 10 ~ 60 seconds | |
| Keyboard State | Saved and Restored | |
| Power Type | USB Interface Power | |
| Dimensions | • 167 x 80 x 28 mm (6.6 x 3.2 x 1.1 in.) | |
| Weight | • 185 g (6.5 oz) | |
| Temperature | • Operating: 0°C ~ 40°C (32°F ~104°F); Storage: -20°C ~ 60°C (-4°F ~140°F) | |
| Humidity | • 0%~90%, Non-Condensing | |
| Certifications | • CE, FCC | |

NETWORKING SOLUTIONS



PACKAGE CONTENTS

- TK-409K
- Multi-Language User's Guide
- Utility CD-ROM
- 4 sets of USB KVM Cables
- 4 sets of Audio/Mic Cables

RELATED PRODUCTS

| TK-209K | 2-Port USB KVM Switch Kit with Audio |
|---------|--------------------------------------|
| TK-407K | 4-Port USB KVM Switch Kit |
| TK-408K | 4-Port PS/2 Audio KVM Switch Kit |

ORDERING INFORMATION

TRENDnet

20675 Manhattan Place, Torrance, CA 90501 USA

Tel: 1-310-961-5500 Fax: 1-310-961-5511 Web: www.trendnet.com Email: sales@trendnet.com

To Order Please Call:

1-888-326-6061

