



CAT5 PS/2 Server Interface Module TK-CAT5P (v1.0R)

- Connects a TRENDnet CAT5 KVM switch to a computer
- Requires an available PS/2 and VGA computer port
- Supports CAT5, 5e and 6 cables
- One TK-CAT5P is required per computer

TRENDnet's CAT5 PS/2 Server Interface Module, model TK-CAT5P, connects a TRENDnet CAT5 KVM switch to a computer with an available PS/2 and VGA port. One TK-CAT5P is required per computer. CAT5, 5e and 6 cable connections are supported.

Features



Computer

Connects a TRENDnet CAT5 KVM switch to a computer



Cable Support

Supports CAT5, 5e, and 6 cable connections



PS/2

Requires an available PS/2 port on the connected computer



VGA

Requires an available VGA port on the connected computer



HD Resolution

Supports resolution up to 1600 x 1200 pixels



OS Support

Supports Windows[®], Linux[™], and Mac[®] operating systems

Specifications

Interface

- 10/100 Mbps Ethernet port (networked to CAT5 KVM switch)
- 2 x PS/2 male connector (Keyboard/Mouse connection to computer)
- VGA male connector (VGA connection to computer)

Resolution

- Up to 1600 x 1200 pixels

Operating Temperature

- 0 – 40 °C (32 – 104 °F)

Operating Humidity

- Max. 90% non-condensing

Dimensions

- Cable length 40 cm (15.7 in.)

Weight

- 54 g (1.9 oz.)

Warranty

- 2 year limited

Certifications

- CE
- FCC

Supported Cables

- CAT5, 5e, 6

Package Contents

- TK-CAT5P