

## Uni-Boot Design Fibre Optic Cable

### Description

As the networking environment of today becomes increasingly dependent on high speed and high density solutions, effective cable management is a real issue. The key concern is how to manage more cable in a smaller amount of space.

Our uniboot fibre patch cord reduces cable management space by 50% compared to standard patch cords. The body of the connector also prevents users from altering the polarity of the patch cord. The patch cord utilises a special "round duplex" cable that allows duplex transmission within a single 3mm cable. As a result of these unique features our uniboot patch cord offers improved airflow and visibility of equipment within a high density network environment.

Our uniboot patch cord is available in a wide variety of cable styles including LSZH, Plenum and Riser.

### Features / Benefits



- ▶ Full duplex in a single 3mm cable
- ▶ Available in OM1, OM2, OM3, OM4 and OS1/OS2 cabled fibre types
- ▶ Available with LSZH, Plenum and riser rated cable
- ▶ Cost effective
- ▶ Save 50% of space in cabinets and cable ways
- ▶ Protects network polarity

### Connector Specification

OPTICAL PERFORMANCE MULTIMODE	SM	MM	CONFORMANCE
Insertion loss (MAX/ ACCEPTANCE)	0.25 dB	0.25 dB	IEC 61300-3-4
Insertion loss (97%)	0.40 dB	0.40 dB	IEC 61300-3-34
Ave/Master	0.18 dB	0.15 dB	IEC 61300-3-4
Ave/Random	0.18 dB	0.20 dB	IEC 61300-3-34

### Cable Specification

CHARACTERISTICS	UNITS	ROUND DUPLEX
Cable Material		LSZH
Strength Member		Aramid
Crush	N100mm	1000
Operating Temperature	°C	-20 to 60
Secondary Buffer Diameter	µm	900+50
Minimum Bending Radius	mm	10D (installed) 20D (loaded)



03 9725 1911



sales@dueltek.com.au



03 9725 1126



Unit 2, 35-43 Lacey St. Croydon  
Victoria 3136 Australia



www.dueltek.com.au