



## VM-1H4C

### 1:4 HDMI Twisted Pair Transmitter & Distribution Amplifier



The VM-1H4C is a high-quality distribution amplifier for HDMI and IR signals over twisted pair cable. It reclocks and equalizes the input signal and distributes it to four TP outputs.

## FEATURES

- **Max. Data Rate** - Supports up to 4.95Gbps (1.65Gbps per graphic channel).
- **HDTV Compatible.**
- **HDCP Compliant.**
- **DGKat™ Signal Integration** - Kramer's unique technology for converting TMDS as well as control and communication to signals that run over twisted pair cables. We strongly recommend using Kramer DGKat™ cables designed specifically for optimum performance.
- **I-EDIDPro™ Kramer Intelligent EDID Processing™** - Intelligent EDID handling & processing algorithm ensures Plug and Play operation for HDMI systems.
- **HDMI Support** - x.v.Color™ and uncompressed audio channels, Dolby TrueHD, DTS-HD.
- **3D Pass-Through.**
- **Kramer Equalization & re-Klocking™ Technology** - Rebuilds the digital signal to travel longer distances.
- **System Range** - Up to 90m (295ft) at 1080i, or up to 30m (98ft) at 1080p on shielded BC-DGKat524 cable. Up to 90m (295ft) at 1080i, or up to 70m (230ft) at 1080p on shielded BC-DGKat623 cable. Up to 100m (330ft) at 1080i or up to 90m (295ft) at 1080p on shielded BC-DGKat7a23 cable.
- **Power Connect** - The VM-1H4C provides power to the twisted pair receivers when they are within 270ft (90m) of the transmitter.
- **Cable** - Requires STP (shielded twisted pair) cable. For optimum range and performance, use Kramer's BC-DGKat524, BC-DGKat623 or BC-DGKat7a23 cables. Note that the transmission range depends on the signal resolution, source device and display used. The distance using non-Kramer CAT 5, CAT 6, and CAT 7 cables may not reach these ranges. Use only shielded cable where both ends of the shield are soldered to ground.
- **Active Input & Output LED Indicators.**
- **Serial Command Handling** - Receives serial commands transparently via the RS-232 port and the TP link.
- **Desktop Size** - Compact size. 2 units can be rack mounted side-by-side in a 1U rack space with an optional RK-1 adapter.



## VM-1H4C

### TECHNICAL SPECIFICATIONS

INPUTS:	1 HDMI connector, 1 IR on a 3.5mm mini jack.
OUTPUTS:	4 twisted pair on RJ-45 connectors.
BANDWIDTH:	Supports up to 4.95Gbps (1.65Gbps per graphic channel).
COMPLIANCE WITH HDMI STANDARD:	Supports HDMI and HDCP.
INDICATOR LEDs:	Power, INPUT, OUTPUT 1, 2, 3 and 4.
POWER CONSUMPTION:	12V DC, 2A.
OPERATING TEMPERATURE:	0° to +55°C (32° to 131°F).
STORAGE TEMPERATURE:	-45° to +72°C (-49° to 162°F).
HUMIDITY:	10% to 90%, RHL non-condensing.
DIMENSIONS:	21.5cm x 16.2cm x 4.4cm (8.5" x 6.38" x 1.7") W, D, H.
WEIGHT:	0.9kg (1.98lbs) approx.
ACCESSORIES:	Power supply.
OPTIONS:	RK-1 19" rack adapter.

