

EDAN



VE-H100B

Veterinary Pulse Oximeter

300 h
SpO₂ Review

100
ID Storage



Easy Operation



Large/Small Size Sensors



Battery Charger Stand



Care for Health

VE-H100B

Veterinary Pulse Oximeter

Mounting Solutions



Bed Rail Mount



Carrying Bag



Charger Stand

- LCD display with backlight control
- Dual work modes: monitoring & spot check
- Numeric display with plethysmogram display
- Trend review
- Pulse-tone modulation (Pitch Tone)
- Adjustable audio and visual alarms
- Powerful data storage capacity (up to 300 hours)
- PatientCare Viewer software for PC data management
- 4 x AA batteries for up to 48 hours of work
- Rechargeable battery for up to 30 hours of work
- Optional battery charger stand
- Automatic power-off function for power saving
- Suitable for feline, canine and other animals

Specification

Classification

Type of Protection	Internally powered equipment (on battery power)
EMC Compliance	Class B
Degree of Protection	Type-BF Applied Part
Mode of Operation	Continuous
Enclosure Degree of Ingress Protection	IPX2

Size and Weight

Size	160 (L)×70 (W)×37.6(H) (mm)
Weight	165 g (without batteries)

Environment

Temperature	
Working	5 °C~40 °C
Storage/Shipping	-20 °C ~55 °C
Humidity	
Working	25%~80% (Non-condensing)
Storage/Shipping	25%~93% (Non-condensing)

Display

Screen Type	LCD (128*64)
-------------	--------------

Charger Stand

Input Voltage	100 to 240 V AC, 50/60 Hz
Output Voltage	6 V DC
Output Current	0.8 A
Output Power	4.8 W

Battery

Ni-MH Rechargeable Battery Package	
Quantity	1
Total Rated Voltage	4.8 V
Capacity	1500 mAh
Typical Battery Life	30 hours
Charge Time	2.5 hours to 80% 4 hours to 100%
Alkaline Batteries	
Typical Battery Life	48 hours (4 x AA batteries)

Measuring Parameter Specification

Measurement Range	
SpO ₂	0-100%
PR	30-350 bpm
SpO ₂ Resolution	1%
PR Resolution	1 bpm

EDAN Edan Instruments, Inc.

- 3/F – B, Nanshan Medical Equipment Park, Nanshan Rd 1019#, Shekou, Nanshan Shenzhen, 518067 P.R. China
- Tel: +86-755-26898326 ■ Fax: +86-755-26898330 ■ www.edan.com.cn ■ Email: info@edan.com.cn

- All rights reserved. Features and specifications are subject to change without notice



ENG-VM-VE-H100B-V1.1-20120809