



355 Hollow Hill Drive Wauconda, IL 60084 Ph: 847.487.4583 Fax: 847.487.0174 E-mail: glueguns@aol.com www.surebonder.com

Specification Sheet #4588 Hair Extension Adhesive

Type: Hot Melt Glue - Polyamide

Solids: 100%

Viscosity ¹: @ 375° (F) (cps) 1,800-2,400

Open Time ²: 25 seconds

Mettler Softening Point ³ 253-266° (F)

Color: Amber

Odor: Slight

Shelf Life: Indefinite

Flash Point: Above 450° (F)

FDA Status: Compositional compliance with FDA Regulation #21CFR175.105 for food packaging.

Storage: Common Storage

Application Temperature: 275°-375° (F)

Suggested Uses: For use in the application of hair extensions.

Precautions: Do Not Mix with other adhesives

Severe burns will result if contact is made in molten state.

Material safety data sheets provide safety precautions that should be observed in handling

and storing.

The buyer should conduct its own tests of this product before use to determine proper preparation technique and suitability for proposed application. FPC warrants that the product conforms with FPC written specifications, and is free from defects. FPC disclaims all other warranties, expressed or implied, including the warranties of merchantability and fitness for a particular purpose. The buyer's sole remedy for non compliance with this warranty shall be for the replacement of the product or refund of the buyer's purchase price.

¹ Brookfield Viscosity – ASTM D3236 using spindle SC4-27

² Open Time – ASTM D4497-94 (1999) – using 45# Kraft paper substrates

³ Mettler Softening Point – ASTM D6493-99