

Revised
December 16th, 2009



9411 Corsair Road
Frankfort IL 60423
(800) 552-0299 Phone
(815) 464-5650 Fax

EMERGENCY PHONE (800) 255-3924
MATERIAL SAFETY DATA SHEET
MP5405 PART A (RESIN)

HMIS	HEALTH 2	FLAMMABILITY 1	REACTIVITY 0
NFPA	HEALTH 2	FIRE HAZARD 1	REACTIVITY 0

1. Chemical Product

Product Name: MP5405 PART A (RESIN)
Product Type: Epoxy Resin

2. Identity of Ingredients

Ingredients	CAS No.	OSHA PEL	ACGIH TLV	Other Limits	%Composition
Reaction product: bisphenol-A- (epichlorohydrin); epoxy resin (number average molecular weight <=700)	25068-38-6	N/A	N/A	N/A	100

3. Hazards identification

Human health hazards: May be irritating to the eyes and skin. Contact with hot material can cause thermal burns. May cause skin sensitization.

Safety hazards: Material will not burn unless preheated.

4. First aid measures

Inhalation: Remove victim to fresh air and provide oxygen if breathing is difficult. Give artificial respiration if not breathing. Get medical attention.

Skin contact: In case of contact with hot product, immediately flood the affected area with cold water. Wipe excess material from exposed area. Flush exposed skin with water and follow by washing with soap if available. Carefully remove clothing; if clothing is stuck to a burn area do not pull it off, but cut around it. Cover burn area do not pull it off, but cut around it. Transport to nearest medical facility for additional treatment.

Eye contact: Flush eye with water. Rest eyes for 30 minutes. If symptoms persist, consult a physician.

Ingestion: Do not induce vomiting. Have victim rinse out mouth with water, then drink sips of water to remove taste from mouth. In general, no treatment is necessary unless large quantities are ingested. However, get medical advice. If vomiting occurs spontaneously, keep head below hips to prevent aspiration.

5. Fire fighting measures

Extinguishing media: Carbon dioxide, dry chemical, foam, or water fog.

Specific hazards during fire fighting: Material will not burn unless preheated. Cool fire exposed containers with water.

Special protective equipment for fire fighters: Do not enter confined fire space without full bunker gear, including a SCBA.

6. Accidental release measures

Spill control: Avoid contact. Evacuate area. Eliminate ignition sources. Ventilate area.

Containment: Dike, contain, and absorb with clay, sand, or other suitable material.

Cleanup: For large spills, pump to storage/salvage vessels. Soak up residue with clay, sand, or other suitable material.

Special procedures: Prevent spill from entering drainage/sewer systems, waterways, and surface waters.

MATERIAL SAFETY DATA SHEET
MP5405 PART A (RESIN)

7. Handling and storage

Handling precautions: Do not get in eyes, on skin or clothing. Wash with soap and water after using and particularly before eating, drinking, smoking, applying cosmetics, or using toilet facilities. Air dry and then launder contaminated clothing and protective gear before reuse. Close container after each use.

Storage: Keep in a cool, dry place. Keep containers closed when not in use. Keep away from open flames and high temperatures.

8. Exposure controls / personal protection

Eye and face protection: Wear safety glasses. Wear coverall chemical splash goggles when eye contact is possible.

Skin protection: Chemical-resistant gloves (i.e. butyl) and other gear as required to prevent skin contact.

Respiratory protection: No respiratory protection is usually required under normal conditions of use.

9. Physical and chemical properties

Specific gravity:	1.17	Boiling point:	> 260°C
Flash point:	249°C	Vapor pressure:	0.03 mbar @ 171°F

10. Stability and reactivity

This material is chemically stable. Hazardous polymerization will not occur.

Conditions to avoid: Avoid high temperatures.

Incompatible materials: Oxidizers, acids, and bases.

11. Toxicological information

Acute oral effects: LD50 > 2000 mg/kg

Acute dermal effects: LD50 > 2000 mg/kg

Sensitization: May cause skin sensitization.

Carcinogenicity: Recent 2-year bioassays in rats and mice exposed dermally yielded no evidence of carcinogenicity.

Mutagenicity: Resins of this type have proved to be inactive when tested by in vivo mutagenicity assays. These resins have shown activity in in vitro microbial mutagenicity screening and have produced chromosomal aberrations in cultured rat liver cells. The significance of these tests to man is unknown.

Inhalation effects: Not expected to be relevant, however, when exposure to vapors or mists is possible, it could cause respiratory tract irritation.

Skin effects: May be mildly irritating. May cause skin sensitization.

Eye effects: May be mildly irritating.

Ingestion effects: Not likely to be a relevant route of exposure.

12. Ecological information

Biodegradability: This section will be completed as ecological reviews are completed.

Toxicity to fish: This section will be completed as ecological reviews are completed.

13. Disposal considerations

Disposal: If this product becomes a waste, it would not be hazardous by RCRA criteria (40 CFR 261). Dispose of according to applicable federal, state, and local regulations.

14. Transport information

Not regulated for transport.

**MATERIAL SAFETY DATA SHEET
MP5405 PART A (RESIN)**

15. Regulatory information

TSCA: All components listed.

DSL: All components listed.

SARA Section 311/312 hazard classes: Chronic health hazard.

California Proposition 65: Contains Phenyl Glycidyl Ether (< 6 PPM), which was listed as carcinogenic on October 1st, 1990.

16. Other information

None

NON-WARRANTY: Information contained herein is based on tests we believe to be reliable and accurate. It is offered in good faith for the benefit of the consumer. Adhesive Systems shall not be liable for any injury, loss, or damage in the use of its chemical products since the conditions of use are beyond our control. In every case we urge and recommend the user conduct tests to determine to their own satisfaction that the product is of acceptable quality and is suitable for their particular purpose under their own operating conditions. Statements concerning the possible use of our products are not intended as recommendations to use our products in the infringement of any patent. Because of changing reporting requirements and other variables it is impossible to guarantee the accuracy of the information contained in this document. It is the responsibility of the user to determine proper personal protection based on the actual condition of use and to comply with all Federal, State, and Local laws and regulations.

Engineering Excellence

For technical information

and support call **1-800-552-0299** or visit our website at

www.instantca.com

Revised
December 16th, 2009



9411 Corsair Road
Frankfort IL 60423
(800) 552-0299 Phone
(815) 464-5650 Fax

EMERGENCY PHONE (800) 255-3924
MATERIAL SAFETY DATA SHEET
MP5405 PART B (HARDENER)

HMIS	HEALTH 3	FLAMMABILITY 1	REACTIVITY 0
NFPA	HEALTH 3	FIRE HAZARD 1	REACTIVITY 0

1. Chemical Product

Product Name: MP5405 PART B (HARDENER)
Product Type: Curing Agent

2. Identity of Ingredients

Ingredients	CAS No.	OSHA PEL	ACGIH TLV	Other Limits	%Composition
Mercaptan/Amine Blend	Trade Secret	N/A	N/A	N/A	90-100

3. Physical/Chemical Characteristics

Boiling Point:	Not Determined
Specific Gravity @ 25°C:	1.11-1.13
Vapor Pressure:	Not Determined
Melting Point:	Not Determined
Vapor Density:	Not Determined
Evaporation Rate:	Not Determined
Solubility in Water:	Negligible (<0.1%)
Appearance and Odor:	Clear to slight amber liquid with mercaptan-like odor.

4. Fire and Explosion Hazard Data

Flash Point:	200°F (PMCC)
Flammable Limits:	LEL=N/D UEL=N/D
Extinguishing Media:	Water fog, foam, dry chemical or CO2.
Special Fire Fighting Procedures:	Wear self contained breathing apparatus. Cool fire-exposed containers with water.
Unusual Fire and Explosion Hazards:	None Known

5. Reactivity Data

Stability:	Stable
Incompatibility:	Oxidizers
Hazardous Polymerization:	Will not occur.
Conditions to Avoid:	No known conditions to avoid.
Hazardous Decomposition:	Oxides of carbon, nitrogen, and sulfur; hydrogen sulfide.

**MATERIAL SAFETY DATA SHEET
MP5405 PART B (HARDENER)**

6. Health Hazard Data

Routes of Entry:	Skin, inhalation, and ingestion
Health Hazards:	(Inhalation) Considered slightly toxic by inhalation. Can cause irritation of respiratory tract and nausea. Overexposure may cause delayed lung injury and chemical pneumonia. (Skin) Causes skin irritation. (Eyes) Causes eye irritation. (Ingestion) Harmful if swallowed.
Carcinogenicity:	Not a known carcinogen.
NTP:	Not a known or anticipated carcinogen.
IARC:	This component has not been classified by the IARC.
OSHA:	Not an OSHA-Regulated Carcinogen.
WHMIS:	D2B
Signs and Symptoms of Exposure:	(Eyes) Redness, swelling, tearing, and hazy vision. (Skin) Redness, swelling, blistering, and itching. (Inhalation) Soreness of the nose and throat, coughing and sneezing. (Ingestion) Pain, vomiting, abdominal tenderness, nausea, blood in vomitus, and blood in feces.
Medical Conditions Aggravated by Exposure:	Preexisting eye, lung, and skin disorders may be aggravated by exposure.
Emergency First Aid Procedures:	(Inhalation) Remove victim to fresh air and provide oxygen if breathing is difficult. Give artificial respiration if not breathing. Get medical attention. (Skin contact) In case of contact, flush with water for at least 15 minutes while removing contaminated clothing and shoes. Get medical attention. (Eye contact) Flush eye with water for at least 15 minutes. Get medical attention. (Ingestion) If swallowed, immediately drink a large quantity of milk or water and call a physician.

NON-WARRANTY: Information contained herein is based on tests we believe to be reliable and accurate. It is offered in good faith for the benefit of the consumer. Adhesive Systems shall not be liable for any injury, loss, or damage in the use of its chemical products since the conditions of use are beyond our control. In every case we urge and recommend the user conduct tests to determine to their own satisfaction that the product is of acceptable quality and is suitable for their particular purpose under their own operating conditions. Statements concerning the possible use of our products are not intended as recommendations to use our products in the infringement of any patent. Because of changing reporting requirements and other variables it is impossible to guarantee the accuracy of the information contained in this document. It is the responsibility of the user to determine proper personal protection based on the actual condition of use and to comply with all Federal, State, and Local laws and regulations.

Engineering Excellence

For technical information
and support call **1-800-552-0299** or visit our website at

www.instantca.com