

# Technical Data Sheet

www.pamfast.com

## PAMFAST ADHESIVES

### UX1502LM

#### DESCRIPTION:

A Low Melt EVA-based hot melt adhesive with excellent hot tack and excellent wetting. It is a white color glue stick that bonds carton, cloth, wood, and craft.

#### PRODUCT SPECIFICATIONS:

SOFTENING POINT (F)	208
VISCOSITY AT 250 (F)	9,800
VISCOSITY AT 350 (F)	1,800
OPEN TIME	10 SECONDS
WORKING TEMPERATURE (F)	250F-300F
COLOR	Opaque

#### APPLICATION:

Can be used in various PAM glue stick guns for Low Melt Adhesives.

#### AVAILABLE FORMS:

½" X 10" sticks in 22 pound cartons.

#### FDA STATUS:

FDA lists product ingredients under CFR 175.105, Adhesives.

**LAST UPDATED August 2008**

**Important Notice:** The details in our sheets and other PAM publications are provided to the best of our knowledge. The contents, however, are not legally binding. In all cases we recommend that preliminary tests be carried out by the customer. In all respects our general terms of sale shall apply.

**Warning:** The molten adhesive and nozzle of the various tools can reach temperatures of up to 400°F. and could cause skin burns if used carelessly. Use appropriate protective gear when working with this material. Always use in well-ventilated area.

The logo for PAM, consisting of the letters "PAM" in a bold, white, sans-serif font, set against a solid orange rectangular background.

**PAM Fastening Technology, Inc.**

2120 Gateway Blvd. • Charlotte, NC 28208

704/394-3141 • Fax 704/394-9339 • email: sales@pamfast.com