

# Technical Data Sheet

www.pamfast.com

## PAMFAST ADHESIVES

### UX1226

\* The last digit in the product's item number indicates its form:

1=1 $\frac{3}{4}$ " plug    2=  $\frac{1}{2}$ " stick    3= $\frac{3}{4}$ " stick    4=granule    5=bulk blocks, pillows, chips  
6=1"x3" plugs    8=PUR cartridge & cleaner cartridge

#### DESCRIPTION:

This temporary pressure sensitive adhesive has a low peel rate and used in release type applications for credit cards, magazine inserts, and etc.

#### PRODUCT SPECIFICATIONS:

VISCOSITY AT 350 (F)	950 cps +/-200
WORKING TEMPERATURE (F)	325-350
Color	Off White to water white
Shelf Life	1 Year

#### APPLICATION:

For best results use in HB 700 Extrusion/Spray tools.

#### AVAILABLE FORMS:

Pellets in 16 ounce and 25 pound bags

#### FDA STATUS:

FDA lists product ingredients under CFR **175.105**, Adhesives;

**176.170** components of the food-contact surface of paper and paperboard in contact with aqueous and fatty foods.

**176.180**, Components of paper and paperboard in contact with dry foods

**LAST UPDATED in May 2006**

**Important Notice:** The details in our sheets and other PAM publications are provided to the best of our knowledge. The contents, however, are not legally binding. In all cases we recommend that preliminary tests be carried out by the customer. In all respects our general terms of sale shall apply.

**Warning:** The molten adhesive and nozzle of the various tools can reach temperatures of up to 400°F. and could cause skin burns if used carelessly. Use appropriate protective gear when working with this material. Always use in well-ventilated area.

The logo for PAM, consisting of the word "PAM" in a bold, white, sans-serif font, set against a solid orange rectangular background.

#### **PAM Fastening Technology, Inc.**

2120 Gateway Blvd. • Charlotte, NC 28208

704/394-3141 • Fax 704/394-9339 • email: sales@pamfast.com