

Technical Data Sheet

www.pamfast.com

PAMFAST ADHESIVES

UX 1402

* The last digit in the product's item number indicates its form:
2= 1/2" stick

DESCRIPTION:

The UX 1402-10 is a light tan, fast setting hot melt in stick form. It was developed for the toughest bonding applications and repairs. Bonds materials such as paper, kraft, cotton fabrics, wood, corrugated board, furniture, and carpeting. This formula is ideal for all woodworking projects where it's bonding strength and set up time of 15-20 seconds can eliminate the use of clamps.

PRODUCT SPECIFICATIONS:

SOFTENING POINT (F)	185
VISCOSITY AT 338 (F)	4,750 cps
OPEN TIME	15-20 SECONDS
TENSILE STRENGTH	330 PSI
ELONGATION	860%
HARDNESS, Shore A	68
WORKING TEMPERATURE (F)	380-400

APPLICATION:

For best results use in PAM Glue Stick Guns.

AVAILABLE FORMS:

1/2" X 10" sticks in 22 pound cartons

FDA STATUS:

FDA lists product ingredients under CFR 175.105, Adhesives.

LAST UPDATED in October 2006

Important Notice: The details in our sheets and other PAM publications are provided to the best of our knowledge. The contents, however, are not legally binding. In all cases we recommend that preliminary tests be carried out by the customer. In all respects our general terms of sale shall apply.

Warning: The molten adhesive and nozzle of the various tools can reach temperatures of up to 400°F. and could cause skin burns if used carelessly. Use appropriate protective gear when working with this material. Always use in well-ventilated area.

The PAM logo consists of the word "PAM" in a bold, white, sans-serif font, set against a solid orange rectangular background.

PAM Fastening Technology, Inc.

2120 Gateway Blvd. • Charlotte, NC 28208

704/394-3141 • Fax 704/394-9339 • email: sales@pamfast.com