

FPC Corporation
355 Hollow Hill Dr.
Wauconda, IL 60084
Tel:847-487-4583
Fax:847-487-0174

Specification Sheet
#708

Type: Hot Melt Glue - Ethylene Vinyl Acetate

Solids: 100%

Viscosity: @ 250°F 37,600 cps

@ 325°F 10,800 cps

@ 350°F 7,600 cps

@ 375°F 5,600 cps

Softening Point: 185/F

Color: TAN

Odor: Slight

Shelf Life: Indefinite

Flash Point: Above 450/F

FDA Status: Compositional compliance with FDA Regulation
#21CFR175.105 for food packaging.

Suggested Uses: Excellent carpet backing adhesive. Resists
cracking at low temperatures and rigid to prevent
"smiling".

Storage: Common Storage

Application Temperature: 250/F to 380/F

Precautions: Do Not Mix with other adhesives
Severe burns will result if contact is made in molten
state.
Material safety data sheets providing safety
precautions that should be observed in handling
and storing.

The buyer should conduct its own tests of this product before use to determine proper preparation technique and suitability for proposed application. FPC warrants that the product conforms with FPC written specifications, and is free from defects. FPC disclaims all other warranties, expressed or implied, including the warranties of merchantability and fitness for a particular purpose. The buyer's sole remedy for non compliance with this warranty shall be for the replacement of the product or refund of the buyer's purchase price.