



Specification Sheet #925

Type: Hot Melt Glue - Ethylene Vinyl Acetate Based

Viscosity ¹: @ 325° (F) (cps) 11,625
@ 350° (F) (cps) 7,750
@ 375° (F) (cps) 5,375

Open Time: Long Open
R & B Softening Point²: 165° (F)
Color: Clear
Odor: Slight
Shelf Life: Indefinite
Flash Point: Above 400° (F)

FDA Status: Compositional compliance with FDA Regulation #21CFR175.105 for food packaging.

Storage: Common Storage

Application Temperature: 350° (F) to 390° (F)

Suggested Uses: A high strength hot melt for multiple applications. Developed for concrete and carpet tack strips, but also bonds to a variety of substrates such as plastic, metal, wood, vinyl, glass and ceramic.

Precautions: Do Not Mix with other adhesives
Severe burns will result if contact is made in molten state.
Material safety data sheets provide safety precautions that should be observed in handling and storing.

The buyer should conduct its own tests of this product before use to determine proper preparation technique and suitability for proposed application. FPC warrants that the product conforms with FPC written specifications, and is free from defects. FPC disclaims all other warranties, expressed or implied, including the warranties of merchantability and fitness for a particular purpose. The buyer's sole remedy for non compliance with this warranty shall be for the replacement of the product or refund of the buyer's purchase price.

¹ Brookfield Viscosity – ASTM D3236

² R & B Softening Point – ASTM E28