

Gluegun.com – (855)437-7700 | www.gluegun.com 24-HOUR EMERGENCY CONTACT NUMBER: 1-877-790-0614

MATERIAL SAFETY DATA SHEET

DATE PUBLISHED: <u>1/15/2013</u>

TRADE NAME: Warren Adhesive HM 6061

MSDS sheets are re-written every (2) year's or/as OSHA, Federal or State regulations are revised.

SYNONYMS: Pressure Sensitive Hot Melt Adhesive

INGREDIENTS

Material or Component	Cas No.	Hazard Data
Naphthenic Distillate		Contains no ingredients subject to
All ingredients are approve		requirements of OSHA Hazard
Under the Federal Regulation 21 CFR 175.105 Standards (29CFR1910.1200)		Communication Standards 29CFR1910.1200

PHYSICAL DATA

Boiling Point:	N/A	Softening Point:	Approx. 185°F
Specific Gravity:	0.98	Vapor Pressure:	N/A
Vapor Density:	N/A	Solubility in Water:	N/A
% Volatiles By Vol.:	N/A	Evaporation Rate:	N/A
Appearance & Odor:	Opaque /Sweet	pH (as is):	N/A

VOC: No levels of volatile organic compound emissions are expected at ambient temperature and pressure. Low molecular weight hydrocarbons may be emitted at application temperature. Monitoring actual plant conditions best develops emission data.

FIRE AND EXPLOSION DATA

Flash Point (Test Method): $>450^{\circ}$ F CoC	Autoignit	ion Temperature :	
Flammable Limits In Air:	N/A	Lower: N/A	Upper: N/A
Extinguishing Media:	CO, cher	nical foam and dry che	emical

Special Fire Fighting Procedures:	Avoid getting water on hot melt to avoid spreading fire.		
Unusual Fire & Explosion Hazard:	None known	Page 2 of A	
Page 2 of 4 <u>HEALTH HAZARD INFORMATION</u>			
Health Hazard Data	Hazard Classification	Source	
Inhalation:	Non to mild irritant	Supplier	
Skin Contact:	Causes severe burns when hot	Supplier	
Skin Absorption:	Non irritant Avoid contact with hot glue	Supplier	
Eye Contact:	Causes severe burns when hot	Supplier	
Ingestion:	Non to mild irritant	Supplier	
EI	FFECTS OF OVEREXPOSURE		
Acute Overexposure:	None at ambient temperatures. Excessive high temperatures may produce irritating fumes.		
Chronic Overexposure:	Unknown		
EMERGE	NCY AND FIRST AID PROCEDURES		
Eyes:	Seek immediate medical attention.		
Skin:	For burns, immerse contact area in cold water immediately. Do not attempt to remove set hot melt from skin.		
Inhalation:	Remove to fresh air.		
Ingestion:	None		

REACTIVITY DATA

Conditions Contributing To Instability:	Stable	
Incompatibility:	Contact with strong oxidizing substances	
Hazardous Decomposition Products:	Thermal decomposition products include CO, CO2 and smoke	
Conditions Contributing To Hazardous Polymerization:	Will not occur	
DISPOSAL, SPILL OR LEAK PROCEDURES		
Aquatic Toxicity:		
Waste Disposal Method:	Dispose of the solid waste in accordance with existing Federal, State and Local regulations.	
Steps To Be Taken If Material Is Released Or Spilled:	Allow to solidify at room temperature, scoop up and put in disposal	

SPECIAL PROTECTION INFORMATION

container.

Ventilation Requirements:

At application temperatures, use of local exhaust is recommended

SPECIFIC PERSONAL PROTECTIVE EQUIPMENT

Respiratory:

No special requirements

Eye:


Safety glasses

Gloves:

Thermally protective gloves

Other Clothing & Equipment:

Cold water source for burns



See Specific Personal Protection section for personal protective equipment recommendations

SPECIAL PRECAUTIONS

Precautionary Statements:	USE EXTREME CARE WHEN WORKING WITH HOT MELTS IN THE HOT MOLTEN, FLUID STATE. SEVERE BURNS CAN RESULT IF SKIN CONTACT OCCURS.
Other Handling And Storage Requirements:	NONE
Additional Regulatory Concerns:	NONE
Federal:	
State:	
Other:	
PREPARED BY:	John S. Warren, Jr.
TITLE:	President
COMPANY:	WARREN ADHESIVES

ADDRESS:

7860 Zeigler Blvd., Mobile, AL 36608