



## TECHNICAL DATA SHEET

# HM 8010

PRODUCT NUMBER

LAST UPDATE: 07/29/11

### HOT MELT PRODUCT

Foam to Foam Applications

### GENERAL INFORMATION

HM-8010 is a slow setting hot melt foam to foam applications. It also exhibits excellent bonds on a wide variety of board and paper. It has good heat stability and medium viscosity for good clean machining on all standard hot melt application equipment.

### PHYSICAL PROPERTIES

Application Temperature	350°F
Color	Beige
Form:	Pillows
Softening Point	220°F
Viscosity @ 350°F	5000 cPs



25 lbs / case (net)  
1750 lbs / pallet (net)

### HANDLING INSTRUCTIONS

To avoid accidental contamination, keep container covered as soon as sufficient hot melt has been removed for use. Do not store in high temperatures.

### SAFETY INSTRUCTIONS

No health hazards are expected with HM-8010 in its solid form. Once melted, it is like any hot liquid in that it can produce severe burns. Care should be taken to avoid getting the hot liquid adhesive on the skin. If this occurs, flush the affected area with large amounts of cold water. Do not try to remove the solidified hot melt. Seek medical attention immediately.

### FDA STATUS

All ingredients in HM-8010 are approved under the Federal regulation 21 CFR 175.105 which related to incidental contact of adhesive with food.

CONSULT MATERIAL SAFETY DATA SHEET FOR FURTHER INFORMATION.  
7860 Zeigler Blvd. P.O. Box 8737 (36689) Mobile, AL 36608  
Phone: 251-633-5034 Fax: 251-633-4210