



SPECIFICATIONS

Product Description: **8" (20.3cm) PLASTIC COM-PAX-IAL BLOWER AC**
 Part Number: **9533, 9533-15, 9533-25**
 Style: **AXIAL FAN 8" (20.3cm) WITH OR WITHOUT CANISTER**

GENERAL DESCRIPTION:

High output from a compact axial blower, designed for easy use and storage without sacrificing airflow. Available as blower only or complete unit with 15' (4.75m) or 25' (7.62m) of ducting and storage canister. Canister attaches to intake or output of blower for suction or ventilation.



CONSTRUCTION:

- Polyethylene housing and canister assembly
- Lightweight, corrosion, UV and chemical resistant
- Super quiet, in "safety orange"
- Bottom enclosure to protect electrical components
- Carry handle molded into blower and canister housing
- Steel powder coated grill



MOTOR:

HP: 1/3 HP
 Certification: UL Listed, CSA Certified
 Voltage/Hz: 115V-230V AC, 50Hz, 60Hz, Single Ø
 RPM: 3400
 Switch: ON/OFF Rocker
 Amps: 4.8A-2.4A (50Hz) / 4.5A-2.2A (60Hz)
 Cord: 20' (6.09m) AWG
 Plug: NEMA 5-15P

FAN:

- Polypropylene nine blade fan

DUCTING: (included on 9533-15 and 9533-25 models)

- Retractable, non-collapsible design
- Single-ply, PVC coated vinyl and polyester materials, temperature resistant up to 180°F (82.2°C)
- Yellow color with black weather strip and integrated nylon attachment strap
- Class 1 hard drawn spring steel wire helix that meets ASTM 227 specs

BLOWER DIMENSIONS:

Blower P/N	Length In (cm)	Width In (cm)	Height In (cm)	Weight Lb (Kg)
9533	13 ¼" (33.6)	12" (30.4)	13 ¾" (34.9)	17 lbs (7.7)
9533-15	32" (81.2)	13 ½" (34.2)	14 ½" (36.83)	33 lbs (14.9)

9533-25	32" (81.2)	13 ½" (34.2)	14½" (36.83)	38 lbs (17.2)
---------	------------	--------------	--------------	---------------

FLOW RATES: (CFM calculated using 15' (4.57m) of 8" (20.3cm) ducting)

Free Air (m ³ /hr)	One 90° Bend (m ³ /hr)	Two 90° Bends (m ³ /hr)
831 CFM (1411.87)	709 CFM (1204.59)	586 CFM (995.62)