

BBS Lighting Force V LED 5600 Kelvin CRI 92

	meters	1.20	2.00	3.00	3.60	5.00	7.00	9.00	12.00
	feet	4.00	6.50	10.00	12.00	17.00	23.00	30.00	40.00
EDLT 19 degree	Lux	55800	24800	8649	6200	3241	1640	992	410
	Fc	5189	2306	804	577	301	153	92	38
EDLT 26 Degree	Lux	31500	14000	4883	3500	1814	926	560	231
	Fc	2930	1302	454	326	169	86	52	21
EDLT 36 degree	Lux	15120	6720	2344	1680	871	444	269	111
	Fc	1406	625	218	156	81	41	25	10
EDLT 50 Degree	Lux	7695	3420	1193	855	443	226	137	57
	Fc	716	318	111	80	41	21	13	5
Standard 19 Degree	Lux	63000	28000	9765	7000	3629	1851	1120	463
	Fc	5859	2604	908	651	337	172	104	43
Standard 36 Degree	Lux	16704	7424	2589	1856	962	491	297	123
	Fc	1553	690	241	173	89	46	28	11
Standard 50 degree	Lux	8712	3872	1350	968	502	256	155	64
	Fc	810	360	126	90	47	24	14	6

115 watt HIGH CRI 92 High Quality LED array containing 100 emitters

BBS Lighting Force V LED 3200 Kelvin CRI 95

	meters	1.20	2.00	3.00	3.60	5.00	7.00	9.00	12.00
	feet	4.00	6.50	10.00	12.00	17.00	23.00	30.00	40.00
EDLT 19 degree	Lux	54000	24000	8370	6000	3110	1587	960	397
	Fc	5022	2232	778	558	289	148	89	37
EDLT 26 Degree	Lux	30600	13600	4743	3400	1763	899	544	225
	Fc	2846	1265	441	316	164	84	51	21
EDLT 36 degree	Lux	14436	6416	2238	1604	832	424	257	106
	Fc	1343	597	208	149	77	39	24	10
EDLT 50 Degree	Lux	7200	3200	1116	800	415	212	128	53
	Fc	670	298	104	74	39	20	12	5
Standard 19 Degree	Lux	57600	25600	8928	6400	3318	1693	1024	423
	Fc	5357	2381	830	595	309	157	95	39
Standard 36 Degree	Lux	16020	7120	2483	1780	923	471	285	118
	Fc	1490	662	231	166	86	44	27	11
Standard 50 degree	Lux	8280	3680	1283	920	477	243	147	61
	Fc	770	342	119	86	44	23	14	6

115 watt HIGH CRI 95 High Quality LED array containing 100 emitters

Average Candela center to edge between the extensive selection of optics is 100% in center to 53 % edge