

POS ACCESSORIES

Customer Display | Scanner | Printer | Cash Drawer

CUSTOMER DISPLAY



Available in
12" & 15" LCD Display



Available in
8" LCD Display

VFD CUSTOMER POLE DISPLAY

- 2 Lines x 20 Characters Vacuum Fluorescent Pole Display
- 40 Characters
- Character Size 5.25 x 9 mm
- Display Colour Green Blue
- ESC/POS (Epson) Emulation
- Long & Short Pole (included)
- Serial/USB Interface
- External Power Supply 12V (included)
- Dimensions:
 - Long 225(W) x 10(D) x 560(H) mm
 - Medium 225(W) x 10(D) x 285(H) mm
 - Short 225(W) x 10(D) x 195(H) mm



BARCODE SCANNER

GSN-320 Handheld CCD Scanner

- Handheld Contact CCD Scanner
- 2,500 pixels CCD
- Scan Rate 150 scans per second
- Designed to withstand 1m drops



ST-351HS Handheld Laser Scanner with Cradle

- Handheld High-Speed Laser Scanner
- Single Line Laser
- Auto Scan in Stand Mode
- Scan Rate 500 scans per second
- Designed to withstand 1m drops
- Available interface keyboard:
RS232/HID USB/USB Virtual COM/OPOS/JPOS



ST-687 Presentation Laser Scanner

- Presentation Dual-Laser Omni-directional Scanner
- 32 Lines Lasers
- Scan Rate 2,400 scans per second (Omni-directional)
- Scan Rate 130 scans per second (single line)
- Designed to withstand 1m drops
- Available interface Keyboard:
RS232/HID USB/USB Virtual COM/OPOS/JPOS

GSN-697 Hands free Orbit Laser Scanner

- Orbit Dual-Laser Omni-directional Scanner
- 650 nm visible laser diode (VLD)
- 5 directions of scan field
- 20 Lines Lasers
- Scan Rate 1,400 scans per second
- Designed to withstand 1m drops
- Available interface keyboard:
RS232/HID USB/USB Virtual COM/OPOS/JPOS



GSN-698 Advanced In-Counter Laser Scanner

- In-Counter Dual-Laser Omni-directional Scanner
- 650 nm visible laser diode (VLD)
- 10 directions of scan field
- 40 Lines Lasers
- Scan Rate 3,600 scans per second
- Available interface keyboard:
RS232/HID USB/USB Virtual COM/OPOS/JPOS



SEVOR

THERMAL RECEIPT PRINTER

TP-250II



- Direct Thermal
- Fast Printing Speed 250mm/sec
- Auto-Cutter with Tear Bar
- High Speed USB 2.0 standard onboard (480Mbps)
- Two Colour Printing (on specially coated Paper)
- 2D Barcode printing support: PDF417, QR-Code
- Internal Buzzer & Water resistant
- Multi-Lingual and Wall Mount Function Available
- Logo & Graphic Printing
- Paper Roll Size: 79.5 +/- 0.5(W) x 83(Max)mm
- Dimension: 145(W) x 195(D) x 146(H)mm
- Available interface: RS232 Serial+USB/LPT Parallel+USB/Ethernet+USB/USB only

TP-150



- Direct Thermal
- Fast Printing Speed 220mm/sec
- Auto-Cutter with Tear Bar
- High Speed USB 2.0 standard onboard (480Mbps)
- 2D Barcode printing support: PDF417, QR-Code
- Internal Buzzer & Water resistant
- Multi-Lingual and Wall Mount Function Available
- Logo & Graphic Printing
- Paper Roll Size: 79.5 +/- 0.5(W) X 83(Max)mm
- Dimension: 144(W) x 184(D) x 120(H)mm
- Available interface: RS232 Serial+USB

DOT MATRIX PRINTER

DP-220

- Serial Impact Method
- Auto Paper Cutter
- Built-in Power Supply
- Print alarm buzzer for noisy places
- Multi-Lingual Available
- Logo and Graphic Printing
- Wall Mount Function Available



- Paper Roll Width 76+/-0.5, 69.5+/-0.5, 57.5+/-0.5mm
- Fast Printing Speed 5.1 LPS (Lines Per Second)
- Auto-Cutter with Tear Bar
- Dimension: 160(W) x 239(D) x 157(H)mm
- Available interface: RS232 Serial/LPT Parallel/Ethernet/USB

CASH DRAWER Heavy duty, rugged, steel construction for demanding environments

C4242/ KC-4141/ KC-4646

- 5 Bills/8 Coins, Removable with Wire Gripper, Stainless steel front panel
- 12V or 24V, 1A(24 ohm) with Micro-Switch
- 3 way Key Lock



Standard/Classic

C4242

- 1 Large Media Slot
- Connector cable 1.50 metres from the bottom of drawer
- Dimension: 420(W) x 420(D) x 90(H)mm
- Available interface: RJ11/USB



Standard/Classic

KC-4141

- 2 Media Slots
- Connector cable 1.50 metres from the top of drawer
- Dimension: 410(W) x 410(D) x 100(H)mm
- Available interface: RJ11



Heavy Duty

KC-4646

- 2 Media Slots
- Connector cable 1.50 metres from the top of drawer
- Dimension: 460(W) x 460(D) x 100(H)mm
- Available interface: RJ11

FT-4617/ C3535

- 1 Media Slot
- 12V or 24V, 1A(24 ohm) with Micro-Switch
- Available interface: RJ11

FT-4617

Flip Top



- 7 Bills/5 Coins
- Connector cable 1.50 metres from the bottom of drawer
- Dimension: 460(W) x 170(D) x 100(H)mm

C3535

Compact



- 4 Bills/4 Coins, Removable with stainless steel top panel
- Connector cable 1.50 metres from the bottom of drawer
- Dimension: 350(W) x 350(D) x 90(H)mm

The Senor Building

65 & 67 Weaver Street
Coopers Plains QLD 4108
Brisbane, Australia
www.senortech.com.au

P: +61 7 3275 5888
F: +61 7 3275 5800
sales@senortech.com.au