



CLEANING ■ SEALING ■ MAINTENANCE

Sealing and maintenance solutions for all types of stone, porcelain, quarry, terracotta and glazed ceramic

MOULDEX TECHNICAL DATA SHEET REF: 25/5

LTP MOULDEX

Grout Cleaner

Kills & removes mould spores, fungus & algae from grouting including the surface of silicone seals and other damp places.

Antibacterial action helps prevent re-growth.

Formulated to cling to surfaces and remove mould spores, fungus, algae and moss from grouting, the surface of silicone seals and other damp places. Antibacterial properties help to prevent re-growth. Ideal for bathrooms and kitchens. Suitable for inside and outside use. Bleaching action helps restore white grouting to its original colour.

Directions for use

SHAKE WELL BEFORE USE. This product contains bleaching action, if in doubt try on an inconspicuous area before general application. Surfaces to be treated should be completely dry before application. Hold upright and spray 5-10 cm from surface. Leave for 45 minutes. Apply a little water and agitate with a stiff brush to release dirt and grime. Rinse thoroughly using a sponge and water.

Stubborn stains and most silicones or elastic grouting will require a longer treatment, in which case apply and leave on surfaces overnight. In case of contact with metals, fabrics and painted surfaces rinse with water immediately.

Do not use with acid based residual grout removers or other acid based cleaners.

Can be used on natural stone and coloured grouting, however always test on an inconspicuous area before general application.

Coverage

5-15 m² depending on size of tile.

Storage information

KEEP UPRIGHT in a cool dry place.

Shelf life: Use within 6 months of purchase for optimum results.

Notes

Important: FOOD ESTABLISHMENTS - Equipment and surfaces subjected to direct food contact must be thoroughly rinsed with potable water after cleaning with this product. Avoid contamination of food during use. Do not store in food processing or food storage area.



This information is offered without guarantee. The material should be used so as to take account of the local conditions and the surfaces to be treated. In case of doubt, the product should be tried out in an inconspicuous area.

for beautiful surfaces we have the solutions...

LTP, Tone Estate, Milverton Road, Wellington, Somerset, TA21 0AN

T +44 (0) 1823 666213 F +44 (0) 1823 665685 E info@ltp-online.co.uk

www.ltp-online.co.uk

April 2014

1





CLEANING ■ SEALING ■ MAINTENANCE

Sealing and maintenance solutions for all types of stone, porcelain, quarry, terracotta and glazed ceramic

MOULDEX TECHNICAL DATA SHEET REF: 25/5

Health, Safety & Environmental

Contains: SODIUM HYPOCHLORITE 2.52% ww

STATUTORY CONDITIONS OF APPROVAL RELATING TO USE

For use only as a surface biocide

Spray onto surfaces from a distance of 10cm

Apply 33-100ml of product per sq/m (each trigger pull releases 0.7-0.9ml of product)

Users must comply in full with all their legal responsibilities under The Control of Pesticides Regulations 1986 (as amended), including complying with all Conditions of Approval

Read all precautions before use

HSE No: 9778

Contains: <5% anionic surfactants. <5% non ionic surfactants. <5% sodium hypochlorite

Ingredients: www.ltp-online.co.uk/dr

To avoid risks to man and the environment comply with the instructions for use:

This material and its container must be disposed of in a safe way

DO NOT CONTAMINATE FOODSTUFFS, EATING UTENSILS OR FOOD CONTACT SURFACES:

Avoid contact with skin. Avoid contact with eyes

In case of contact with eyes rinse immediately with plenty of water & seek medical advice.

Health, Safety & Environmental (continued)

Do not breathe spray. Use only in well ventilated areas.

Do not contaminate ground, waterbodies or watercourses with chemicals or used container.

REMOVE OR COVER ALL FISH TANKS AND BOWLS before application.

KEEP AWAY FROM TREATED SURFACES UNTIL DRY. Do not empty into drains.

WASH HANDS AND EXPOSED SKIN before meals and after use

KEEP UPRIGHT IN A SAFE PLACE. Keep out of reach of children.

If swallowed seek medical advice immediately and show this container or label.

CONTACT WITH ACIDS LIBERATES TOXIC GAS.

This product must not be mixed with other chemical substrates.



This information is offered without guarantee. The material should be used so as to take account of the local conditions and the surfaces to be treated. In case of doubt, the product should be tried out in an inconspicuous area.

for beautiful surfaces we have the solutions...

LTP, Tone Estate, Milverton Road, Wellington, Somerset, TA21 0AN

T +44 (0) 1823 666213 F +44 (0) 1823 665685 E info@ltp-online.co.uk

www.ltp-online.co.uk

April 2014

2

