

TL 90 Series T8 Fluorescent Lamps

Unmatched color rendering in
T8 fluorescent technology



Ideal for...

- High-End Retail Shops
- Hotel Ballrooms and Restrooms
- Museums and Art Galleries
- Graphic Arts/Photography Studios



- **Perfect for Color
Critical Applications**

Provides distortion-free
fluorescent lighting

- **3000K with 95 CRI**

- **5000K with 98 CRI**

- **Damage Factor
Comparable to
Incandescent Sources**

Glass composition ensures low
UV content, protecting sensitive
articles and dyes

- **Available in 2', 3'
and 4' Lengths**



Philips Lighting Company
 200 Franklin Square Drive • P.O. Box 6800
 Somerset, NJ 08875-6800
 1-800-555-0050

www.lighting.philips.com/nam

A Division of Philips Electronics North America Corporation
 Printed in USA 3/02 P-5037-D

Philips Lighting
 281 Hillmount Road
 Markham, Ontario L6C 2S3
 A Division of Philips Electronics Limited

TL 90 Series T8 Fluorescent Lamps

Electrical, Technical and Ordering Data (Subject to change without notice)

Product Number	Description	Nom. Watts	Bulb	Base	Std. Pkg. Qty.	Color Temp. (Kelvin)	CRI	Approx. Initial Lumens	Design Lumens ⁽¹⁾	Nom. Length (In.)	Rated Avg. Life (Hrs.) ⁽²⁾
22083-0	F17T8/TL930	17	T8	Med. Bi-pin	25	3000	95	910	850	24	20,000
22154-9	F17T8/TL950	17	T8	Med. Bi-pin	25	5000	98	910	850	24	20,000
22158-0	F25T8/TL930	25	T8	Med. Bi-pin	25	3000	95	1550	1450	36	20,000
22159-8	F25T8/TL950	25	T8	Med. Bi-pin	25	5000	98	1550	1450	36	20,000
20904-9	F32T8/TL930	32	T8	Med. Bi-pin	25	3000	95	2000	1860	48	20,000
20905-6	F32T8/TL950	32	T8	Med. Bi-pin	25	5000	98	2000	1860	48	20,000

(1) Approximate lumens at 40% of rated average life (4,000 hours).

(2) Average life under specified test conditions with lamps turned off and restarted once every three operating hours.

Spectral Power Distribution

