



MSR Gold™ MiniFastFit (DJ/Club)

MSR Gold™ 300/2 MiniFastFit 1CT/4

Thanks to the specially designed lamp base and lamp holder, the MSR Gold™ MiniFastFit takes just seconds to replace, to help ensure non-stop clubbing entertainment. In addition, the innovative gold plated pins ensure excellent current transfer to prolong lamp and lamp holder lifetimes and thereby reduce lamp replacement costs. Easy handling and small compact fixture designs are allowed by the lamps compact size, while the very short arc provides a high perceived brightness and high beam intensity.

Warnings and Safety

- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Product data

General information		Luminous Efficacy (Rated) (Min)		64 lm/W
Cap-Base	PGJX28 [PGJX28]	Luminous Efficacy (rated) (Nom)		75 lm/W
Operating Position	UNIVERSAL [Any or Universal (U)]	Color Rendering Index (Nom)		78
Main Application	Entertainment	Operating and electrical		
Life to 50% Failures (Nom)	750 h	Power (Nom)	300 W	
System Description	MiniFastFit	Lamp Current (Nom)	3.75 A	
Light technical		Ignition Supply Voltage (Min)	207 V	
Color Code	2	Controls and dimming		
Luminous Flux (Nom)	22700 lm	Dimmable	Yes	
Chromaticity Coordinate X (Nom)	288			
Chromaticity Coordinate Y (Nom)	306			
Correlated Color Temperature (Nom)	9300 K			

MSR Gold™ MiniFastFit (DJ/Club)

Mechanical and housing		Order product name	
Cap-Base Information	PGJX28	MSR Gold™ 300/2 MiniFastFit 1CT/4	
Luminaire design requirements		EAN/UPC - Product	
Bulb Temperature (Max)	950 °C	8718291221111	
Pinch Temperature (Max)	500 °C	Order code	
Pinch Temperature (Max)-DUP(do not use)	500 °C	928177105115	
Product data		Numerator - Quantity Per Pack	
Full product code	871829122111100	1	
		Numerator - Packs per outer box	
		4	
		Material Nr. (12NC)	
		928177105115	
		Net Weight (Piece)	
		0.062 kg	

Dimensional drawing



Product	D (max)	O	L (min)	L (max)	L	C (max)
MSR Gold™ 300/2 MiniFastFit 1CT/4	23 mm	5.0 mm	65.8 mm	67.8 mm	66.8 mm	126 mm

MSR Gold™ 300/2 MiniFastFit 1CT/4

