Product datasheet



FLK/X 115V



Product features and benefits

- Robust construction for reliable, lasting performance
- Consistent color over the life of the lamps
- Instant on and nearly constant luminous flux over the life of the lamp
- Broad product portfolio supporting the stage and studio markets
- Dimmable with traditional amber shift

Areas of application

- Stage and theatre
- Studio, TV and film
- Professional Photography
- Club & Disco

Product datasheet

Technical data

General product information

Product Number	54551			
Product Name	FLKX 115V 12/CS 1/SKU			
Ordering Abbreviation	FLK/X 115V			
Brand Name	OSRAM			
Family Brand Name	FLK			
General Description	575W tungsten halogen, medium to low voltage, single ended			
Application	Stage & Studio			

Electrical data

Nominal Wattage	575 W	
Nominal Voltage	115 V	
Type of Current	AC	

Light technical data

Luminous Flux	10000 lm		
Light Center Length - LCL (in)	2.325 in		
Light Center Length - LCL (mm)	59.055 mm		
Color Temperature	3200 K		
Color Rendering Index	100		
Average Rated Life	2000 h		

Physical attributes

Base	G9.5 Medium Bipin		
Bulb Shape	T5		
Maximum Overall Length (in)	3.976 in		
Maximum Overall Length (mm)	101 mm		
Length l (in)	3.976 in		
Length I (mm)	101 mm		
Length I max. (in)	3.976 in		
Length I max. (mm)	101 mm		
Diameter d (in)	0.625 in		
Diameter d (mm)	15.88 mm		
Distance a (in)	2.325 in		
Distance a (mm)	59.055 mm		
Filament	CC-8		

Product datasheet

Filament Dimensions Length (in)	0.6250 in	
Filament Dimensions Length (mm)	15.88 mm	
Filament Dimensions Width (in)	0.425 in	
Filament Dimensions Width (mm)	10.795 mm	

Additional product data

Operating Position	Any
Total surface inside 1: appearance (cold)	Clear
Class	C (gas)
Lamp Type	SINGLE END

Packaging Information

Product number	EAN/UPC	Packaging	Quantity	Outside dimensions l x w x h	Gross weight
54551	0046135545511	Folding box (SKU)	1		
54551	10046135545518	Shipping box (Case)	12	7 in x 5.4 in x 6 in	1.8 lb

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

OSRAM does not accept liability for errors, changes and omissions.