

Par Series

Sunlite 80542 LED PAR16 Long Neck Recessed Spotlight Bulb, 7 Watt, (75W Halogen Replacement), 500 Lumens, Medium (E26) Base, Dimmable, ETL Listed, 4000K Cool White, 1 Pack

High Efficiency

DESCRIPTION:

From the moment you switch on our PAR16 longneck led bulbs, they will produce a flicker-free dimmable light. These bulbs are the perfect option for setting the tone in your living room, kitchen, or bedroom. With its direct targeted brightness, our led bulbs will create a unique style and ambiance in every room of your home! With these par16 led bulbs, you will save up to 75% on your annual energy bill, instantly providing you with substantial savings. They have a lifespan of 25,000 hours and will reduce the hassle of replacing difficult-to-reach bulbs. Sunlite features the highest quality bulbs and fixtures designed to meet your home, office, or workplace needs. We are committed to providing our customers with outstanding service, expertise, and durable products. Our led PAR16 light bulbs are a worry-free choice, backed by our 3-year manufacturer warranty.

FEATURES:

- UPGRADE TO LED Easily upgrade your old incandescent bulbs with energy-efficient led technology. Please shop with confidence as our PAR16 longneck led bulbs are backed by a 3 Year manufacturer warranty
- ENERGY EFFICIENT Featuring a 35° beam angle, each bulb puts out a bright 500 lumens of light while only using 7 watts of electricity. Annual yearly energy costs are a low \$0.84 (Based on 3 hours/day at \$0.11/kWh)
- DIMMABLE Emits a dimmable and vibrant, Cool white light at 4000K. Ideal for recessed lighting, track lighting, and other fixtures with an intermediate (E17) base. High Color Rendering Index rating of 80 for more vivid and true colors
- LONG LIFE With a life span of up to 25,000 hours, you will replace difficult-to-access bulbs less often. You will save maintenance costs and save energy at the same time
- ETL LISTED These LED bulbs are ETL Listed and tested to meet their rigorous safety standards. Unlike incandescent bulbs, they contain no harmful chemicals and do not require special handling or disposal



sunlite

General Characteristics

Average Rated Hours

Ingress Protection

Average Life Span Years

Bulb Shape

Dimmable

Material

Base

Prod	luct D	imen	sions

MOL (in)	3.03
Diameter (in)	1.97
Item Dimension (in)	(W) 1.96 (H) 3.08 (D) 1.96
Package Dimension (in)	(W) 2 (H) 3.45 (D) 2
Package Weight (lb)	0.14

Product Data

Case Unit Rate	6
Pack Size	1
Item UPC	653703805429
Warranty Years	BX
Package Type	Box

Electrical Characteristics

Watts	7
Volts	120
Equivalent Wattage	75
LED Chip Manufacturer	Bridgelux
Power Factor	0.7
Temperature	?20~45?

Light Characteristics

Lumens Brightness 5	00
Color Rendering Index CRI 8	0
CBCP 1.	231
Emitted Color C	ool White
Color Temperature Kelvin 4	000K
Beam Angle 3	5°
Flicker n	0

Additional Features

Safety Rating Mark

ETL - Damp Location



744 Clinton Street Brooklyn, NY, 11231 | 718.768.7000



PAR16 25000 Medium Screw (E26) 23 IP20 (12.5 mm solids, Not protected from liquids) Yes Plastic & Aluminum