



Sunlite's LED flat panels are usually used to replace 2X2, 1X4 and 2X4 fluorescent fixtures. It's slim design is a easy installation to lay in drop ceilings.

- Compatible with most wall based 0-10 volt dimming controllers

General Characteristics

Fixture Life Hours	50000 Hours
Bulb Type	Integrated
Material	Aluminum
Lens	Center Basket
Lens Finish	White
Finish	White
Life (based on 3hr/day)	45.7000000000
Safety Rating	UL Listed - Damp Location
Dimmable	True
Dimming Type	0-10V Low Voltage

Electrical Characteristics

Watts	30
Volts	120-277
LED Chip Manufacturer	LG 5630 + ESPEN driver

Light Characteristics

Brightness	3750 Lumens
Color Accuracy (CRI)	80
Light Appearance	Neutral White
Color Temperature	3500K

Product Dimensions

Size	2X2
Item Dimensions (in)	(W) 24 (H) 3.6 (D) 24

Product Data

Item Number	85135-SU
Barcode on SKU	653703851358
Brand	Sunlite
Description	LFX/2X2/30W/D/MV/35K
DLC File Number	PLEYXCGM0QX3

Additional Features

UL RATING	UL Listed - Damp Location
-----------	---------------------------

Fixture Characteristics

Style	Troffer
Shape	Square
Number of Lights	1 - Light
Mounting	Recessed
Use Location	Indoor