



## Sunlite 85462-SU LED 2-Pack 1x4 Foot Lay-in Light Panel Fixtures, Color Tunable 35K/40K/50K, Power Adjustable 20W/30W/40W, 3600-4520 Lumens, 120/277 Volt, 0-10V Dimmable, UL & DLC Listed, 1 by 4 FT

Sunlite 2-Pack LED Lay-in Light Panel Fixtures are a long life, energy efficient replacement for fluorescent fixtures. These color and power tunable fixtures features innovative technology that allows you to choose the color temperature and light output at the time of installation. Select 3500K Neutral White, 4000K Cool White, or 5000K Super White depending on your preference using a switch located on the back. A second switch allows you to select between wattage for different lumen outputs. Choose 20 watts, 30 watts, or 40 watts. White finish and opaque diffuser for even light distribution. These fixtures have a built-in 120/277 volt dimmable driver for use with low voltage (0-10V) dimming controls. No maintenance, 50,000 hour life span LED technology for years of maintenance free service. UL and DLC Listed.

- LED LIGHT PANELS - LED Lay-in Light Panel Fixtures are a long life, energy efficient replacement for fluorescent fixtures. Designed for installation into 1X4-foot drop ceiling grids.
- COLOR AND POWER TUNABLE - These fixtures allow you to choose the color temperature at the time of installation. Select 3500K Neutral White, 4000K Cool White, or 5000K Super White depending on your preference using a switch located on the back. A second switch allows you to select between wattage for different lumen outputs. Choose 20 watts, 30 watts, or 40 watts.
- DIMMABLE - These fixtures can be dimmed when attached to a low voltage (0-10V) dimming control. Range is 100-10%.
- LONG LIFE - Provides up to 50,000 hours energy efficient light. No maintenance, long-life LED technology means you won't need to climb ladders to replace difficult to reach bulbs.
- UL Listed - UL Listed for safety and quality. DLC listed for design and efficiency. Great for commercial or residential applications on 120/277 volt service.

### General Characteristics

Fixture Life Hours	50000 Hours
Material	Aluminum
Lens Finish	White
Finish	White
Life (based on 3hr/day)	45.7000000000
Safety Rating	UL Listed
Ingress Protection	IP20 (12.5 mm solids, Not protected from liquids)
Dimmable	True
Dimming Type	0-10V Low Voltage

### Electrical Characteristics

Watts	20/30/40
Volts	100-277
LED Chip Manufacturer	4014
Power Factor	0.9
Operating Temperature	+10 to +40 °C

### Light Characteristics

Brightness	4320/4600/4400 Lumens
Color Accuracy (CRI)	80
Light Appearance	CCT Tunable
Color Temperature	35K/40K/50K
Beam Angle	120°

### Product Dimensions

Size	1X4
Item Dimensions (in)	(W) 11.81 (H) 0.39 (D) 47.8

### Product Data

Item Number	85462-SU
Case Quantity	1.000000
Pack Size	2 Pack
Barcode on SKU	653703854625
Brand	Sunlite
Description	LFX/1X4/SCT/MW/D/MV/0-10V/2PK
DLC File Number	PJJ2K0RZ

### Additional Features

UL RATING	UL Listed
-----------	-----------

### Fixture Characteristics

Style	Flat
Shape	Rectangle
Number of Lights	1 - Light
Mounting	Recessed



SALE on Sunlite @ [www.BulbAmerica.com](http://www.BulbAmerica.com)  
take additional 5% Off with coupon code 5PDF

**Item: 85462-SU**  
**LFX/1X4/SCT/MW/D/MV/0-10V/2PK**

*Use Location*

*Indoor*