
Product datasheet

HALOSTAR STARLITE 10 W 12.0 V G4

HALOSTAR STARLITE | Low-voltage halogen lamps with pin base



- General illumination Entrance lighting Accent lighting Lighting for reading Garden lighting Shops Restaurants, hotels and similar prestigious applications Offices, public buildings Outdoor applications only in suitable luminaires

- Brilliant accent light Incredibly small dimensions for revolutionary new luminaire designs Approved for use in open luminaires (to IEC 60598-1) Axial filament for optimum directional light Special pins for corrosion protection UV filter Contains no mercury
- Product features Average life: 2,000 h 100 % dimmable Color rendering index Ra: 100Product benefits Brilliant accent light Incredibly small dimensions for revolutionary new luminaire designs Approved for use in open luminaires (to IEC 60598-1) Axial filament for optimum directional light Special pins for corrosion protection UV filter Contains no mercuryAreas of application General illumination Entrance lighting Accent lighting Lighting for reading Garden lighting Shops Restaurants, hotels and similar prestigious applications Offices, public buildings Outdoor applications only in suitable luminaires

Product datasheet

Technical data

Electrical data

Nominal wattage	10.00 W
Nominal voltage	12 V
Rated wattage	10.00 W
Claimed equiv. conventional lamp power	10 W


Photometrical data

Nominal luminous flux	145 lm
Light color (designation)	Warm White
Rated luminous flux	145 lm
Rated color temperature	2800 K
Color rendering index Ra	100
Color temperature	2800 K
Luminous flux	145 lm

Light technical data

Starting time	0.0 s
---------------	-------

Dimensions & weight



Diameter	10.0 mm
Overall length	33.0 mm
Light center length (LCL)	22.0 mm
Length	33.0 mm
Outer bulb	T10
Product weight	1.10 g

Lifespan

Product datasheet

Rated lamp life time	2000 h
Number of switching cycles	50000

Additional product data

Base (standard designation)	G4
Mercury content	0.0 mg
Mercury-free	Yes

Capabilities

Burning position	Any
Dimmable	Yes

Certificates & standards

Energy efficiency class	C
Energy consumption	11 kWh/1000h

Country specific categorizations

ILCOS	HSGS/C/AXUB-10-12-G4-10/22
Order reference	64415 S AX 10W

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4058075094178	HALOSTAR STARLITE 10 W 12.0 V G4	Shipping carton box 40 Pieces Unpacked	144 mm x 107 mm x 121 mm	1.86 dm ³	165.00 g
4058075103658	HALOSTAR STARLITE 10 W 12.0 V G4	Shipping carton box 5000 Pieces Unpacked	410 mm x 310 mm x 435 mm	55.29 dm ³	7875.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

Product datasheet

OSRAM is distribution partner
of LEDVANCE of LAMPS

OSRAM

OSRAM GmbH
Marcel-Breuer-Strasse 6
80807 Munich, Germany