



TUV PL-S - Compact solution for residential applications

TUV PL-S

TUV PL-S lamps are compact UVC (germicidal) lamps used in residential water and air disinfection units. The compact size of the lamp allows for a small system design and design flexibility. TUV PL-S lamps offer constant UV output over their complete lifetime, for maximum security of disinfection and high system efficacy. Thanks to the single-ended lamp base, lamp replacement is easy.

Benefits

- · Security of effective disinfection over the useful lifetime of the lamp
- High system efficacy because it is not required to over-design the purification system to maintain effectiveness of disinfection
- · Good environmental choice because of lowest amount of mercury

Features

- · Short-wave UV radiation with a peak at 253.7 nm (UVC) for disinfection purposes
- $\boldsymbol{\cdot}$ Protective inside coating ensures constant UV output over the complete lifetime of the lamp
- · Lamp glass filters out the 185 nm ozone-forming radiation
- 2-Pin PL-S lamp base contains a special starter for almost instant starting on electromagnetic drivers
- · 4-Pin PL-S lamps are designed for use on electronic drivers
- · Warning sign on lamp indicates that the lamp radiates UVC

Application

- Deactivation of bacteria, viruses and other micro-organisms
- · Residential drinking water units
- · Pond water units
- · Air treatment units
- · Stand-alone purifiers


Warnings and Safety

- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.
- DANGER: Risk Group 3 Ultra Violet product. These lamps emit high-power UV radiation that can cause severe injury to skin and eyes. Avoid eye and skin exposure to unshielded product. Use only in an enclosed environment which shields users from the radiation.

Versions








TUV PL-S 2G7

Dimensional drawing

Product	D1 (max)	D (max)	A (max)	B (max)	C (max)
TUV PL-S 5W/2P 1CT/6X10BOX	13 mm	28 mm	67 mm	83 mm	105 mm
TUV PL-S 9W/2P 1CT/6X10BOX	13 mm	28 mm	129 mm	144.5 mm	167 mm

TUV PL-S

Dimensional drawing



Product

TUV PL-S 9W/4P 1CT/6X10BOX

Approval and Application	
Mercury (Hg) Content (Nom)	3.0 mg
General Information	
Useful Life (Nom)	9000 h
Main Application	Disinfection
Light Technical	
Color Code	TUV
Color Designation	-
Lumen Depreciation At Useful Lifetime	20 %
Mechanical and Housing	
Bulb Shape	2xT12

Operating and Electrical

		Lamp Current	Voltage	Power (Rated)
Order Code	Full Product Name	(Nom)	(Nom)	(Nom)
381863	TUV PL-S 5W	0.18 A	34 V	5.5 W
325126	PL-S 9W/TUV 60PK	0.17 A	60 V	9 W

		Lamp Current	Voltage	Power (Rated)
Order Code	Full Product Name	(Nom)	(Nom)	(Nom)
285668	TUV PL-S 9W/4P 1CT/	0.17 A	60 V	8.6 W
	6X10BOX			

General Information

Order Code	Full Product Name	Cap-Base
381863	TUV PL-S 5W	G23



© 2020 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The

TUV PL-S

Order Code	Full Product Name	Cap-Base
325126	PL-S 9W/TUV 60PK	G23
285668	TUV PL-S 9W/4P 1CT/6X10BOX	2G7

UV

Order Code	Full Product Name	UV-C Radiation
381863	TUV PL-S 5W	1.1 W
325126	PL-S 9W/TUV 60PK	2.3 W

Order Code	Full Product Name	UV-C Radiation
285668	TUV PL-S 9W/4P 1CT/6X10BOX	2.3 W



© 2020 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as a warranty after the first and the