Accuracy International AXMC

2014 Model

Calibre:	.338 Lapua / .300 Win mag /.308 Winchester (Long action)
Weight:	6.6Kg (14.6lb) (Empty magazine, no scope, 27" barrel with muzzle brake)
Dimensions:	1225mm x 180mm x 90mm (Stock folded 965mm x 180mm x 100mm) (27" barrel, no scope)

Features:

- Proofed steel action featuring AI's patent pending Quickloc quick release barrel system, bolted and bonded to aluminium chassis
- 30MOA STANAG 4694/Mil Std 1913 action and forend rail
- 6 lug, 60 degree bolt with AI combat proven leaf spring extractor
- 3 position safety
- Two stage trigger adjustable for trigger weight between 1.5 and 2Kg
- Detachable 10-round CIP length double stack magazine- can also be top loaded though the rifle ejection port
- Left side magazine port cut out for ease of magazine insertion

Base models:

- Right side folding stock over bolt, adjustable cheekpiece, adjustable buttpad with spacers, pistol grip, flush cup sling attachment points, 30MOA STANAG 4694/Mil Std 1913 action rail and 16" forend tube and rail, double chamber standard muzzle brake, 1 x 140mm plain accessory rail, 2 x 80mm flush cup accessory rails, user manual, 1 x 10 round double stack CIP magazine. Colours – Black or green stocksides with black metalwork or pale brown stocksides and metalwork.

Factory Barrel Options:

- .338 LM – 20"/27" 1 in 9.35" twist, stainless steel, plain threaded for muzzle brake
- .300 Win Mag – 20"/24"/26" 1 in 11" twist, stainless steel, plain threaded for muzzle brake
- .308 Win– 20"/24"/26" 1 in 12" twist, stainless steel, plain threaded for muzzle brake

Options:

- Tactical threaded double chamber muzzle brake for AI suppressor

Accessories

- STANAG 4694 / Mil std 1913 accessory rails to attach to AI's patent pending KeySlot™ mounting system
- Bipods and rear butt spikes
- Calibre conversion kits
- Harris bipod mount
- Handstop with sling loop and Flush cup
- Suppressor
- Slings
- Transit cases
- Cleaning kits