

T5L 1054 1000W REPLACEMENT

T5HO Aluminum or Steel
High-Bay Industrial Fixtures



HiMax Energy Saving High-Performance
Fluorescent Lighting Systems

FEATURES & BENEFITS

- **Patented Push-Button Access** - AEI leads the industry with access to all internal components without the use of tools. Lamp tray swings out of the way without removing lamps for access to the ballast compartment.
- **Over 50% Energy Savings Compared to HID** - T5HO lamps and ballasts save more than 50% over older HID and T12 Fluorescent lighting systems.
- **Longer Lamp Life For T5HO!** T5HO lamps are rated for up to 35,000 hours, nearly twice that of typical fluorescent and HID lamps.
- **95% Lumen Maintenance For T5HO** - HID light levels drop as much as 60% as the lamps age. T5HO light levels maintain 95% over the life of the lamp.
- **Instant On...Instant Restrike...No Flicker!** T5HO ballast technology eliminates flicker and provides instant on and instant restrike while maintaining light levels during dips and peaks.
- **Cool Operation** - Vented aluminum housing construction provides optimal ballast performance and long life.
- **Color Quality and Consistency** - T5HO lamps are 80CRI or greater, providing excellent color quality over the life of the lamp, thus enhancing visual comfort.
- **Factory Installed Occupancy Sensors** - Auto on/off functions are available for energy savings and extended life using integral sensor design.

SPECIFICATIONS

CONSTRUCTION: Aluminum Housing standard. Code Gauge Post-Powdercoat CRS Housing is optional. Housing is vented to keep ballast cool in a wide range of operating temperatures.

REFLECTOR DESIGN: Specular Miro4® reflectors standard. White reflectors are optional. Consult AEI for other reflector options.

ELECTRICAL: 120 or 277V, 75°C programmed start ballasts standard. Universal voltage or 347, 480V and 90°C ballasts as well as other options are available upon request. Emergency ballasts available.

MOUNTING: Surface, Chain or Pendant mounting options available. See our Labor Saving Installation Guide for mounting designs.

LISTING: UL Listed for Damp Locations.

Featuring "Pat'd Push Button Access"



Step 1. Place your thumbs on the buttons

Step 2. Press thumbs on buttons releasing center assembly


Step 3. Rest assembly at 90 degrees

EASY ACCESS
No Parts To Drop
REDUCED LABOR
Opens In Seconds
SAVES MONEY
Exclusive Features




DIMENSIONS

Wireway access in seconds without removing lamps or use of any tools!



T5L-AL/CRS-1054
Length Width Height
46.93" 26.13" 4.00"

INSTALLATION DIAGRAM



*Dimensions are subject to change without notice. Consult factory for details.

ORDERING GUIDE



BRINGING YOU OUT OF THE DARK AGES!

Fixture Model

Housing

Of Lamps
Wattage

Voltage

Lamp Color

Options

Mounting

T5L

1054

CONSULT
AEILighting.com
for
Photometric
Information
On This
Fixture

HOUSING TYPE

AL=Aluminum
CRS=Cold Rolled Steel

OF LAMPS

10=10 Lamps

WATTAGE

54=54W 4-foot Nominal Length
Consult Factory When Application
Requires Other Wattages

VOLTAGE

12=120V 27=277V
34=347V 48=480V
UNI=120-277V 90C=120-277V 90°C

Leave Blank if No Lamps

30=3000K 35=3500K
41=4100K 50=5000K 65=6500K

SENSORS

OCL=Alsle Sensor OCG=360 Degree Sensor
OCLT=360 Degree Low Temp. Sensor
Consult Factory For More Options

CORDS / PLUGS

X'C=Length + Cord Only
X'CP=Length/Cord + Style/Plug
Consult Factory For More Options

BALLASTS

EMXXX=Emergency Ballast/Lumens
DIM=Dimming Ballast
Consult Factory For More Options

REFLECTORS

UL=Uplight
WH=White Reflector WG=Wire Guard

OTHER

CTD=Cooled Lamps, TG=Tube Guards
CST=Custom
Consult Factory For Custom
Applications and Ordering Number

Mounting

VH=V-Hook HK=3/4" Hook
GPLX=Grippler + Style (L,S,T,Y)
Consult Options Guidelines For
Grippler Details
HUB=3/4" Hub
X'ST=Length + Galvanized Stem
SB=3/4" Slide Box Assembly
Hub and Stem Optional
SP=3/4" Single Point Bracket
Hub and Stem Optional

AEI LIGHTING INC.
1113 West Birchwood Avenue
Mesa, AZ 85210
TEL 480.733.6594
FAX 480.733.6596
WEB www.aeilighting.com

Project Name _____ Fixture Type _____

Catalog # _____ Quantity _____

ADVANCED ENERGY IDEAS, INC.

T5L 1054