T5L 254 35

T5HO Aluminum or Steel High-Bay Industrial Fixtures



- Patented Push-Button Access AEI leads the industry with access to all internal components without the use of tools. Lamp tray swings out of the way without removing lamps for access to the ballast compartment.
- Over 50% Energy Savings Compared to HID -T5HO lamps and ballasts save more than 50% over older HID and T12 Fluorescent lighting systems.
- Longer Lamp Life For T5HO! T5HO lamps are rated for up to 35,000 hours, nearly twice that of typical fluorescent and HID lamps.
- •95% Lumen Maintenance For T5HO HID light levels drop as much as 60% as the lamps age. T5HO light levels maintain 95% over the life of the lamp.
- Instant On...Instant Restrike...No Flicker! T5HO ballast technology eliminates flicker and provides instant on and instant restrike while maintaining light levels during dips and peaks.
- Cool Operation Vented aluminum housing construction provides optimal ballast performance and long life.
- Color Quality and Consistency T5HO lamps are 80CRI or greater, providing excellent color quality over the life of the lamp, thus enhancing visual comfort.
- Factory Installed Occupancy Sensors Auto on/off functions are available for energy savings and extended life using integral sensor design.

SPECIFICATIONS

CONSTRUCTION: Aluminum Housing standard. Code Gauge Post-Powdercoat CRS Housing is optional. Housing is vented to keep ballast cool in a wide range of operating temperatures.

REFLECTOR DESIGN: Specular Miro4® reflectors standard. White reflectors are optional. Consult AEI for other reflector options.

ELECTRICAL: 120 or 277V, 75°C programmed start ballasts standard. Universal voltage or 347, 480V and 90°C ballasts as well as other options are available upon request. Emergency ballasts available.

MOUNTING: Surface, Chain or Pendant mounting options available. See our Labor Saving Installation Guide for mounting designs.

LISTING: UL Listed for Damp Locations.

Featuring "Pat'd Push Button Access" **EASY ACCESS REDUCED LABOR** Opens In Seconds SAVES MONEY Step 1. Place your thumbs on the buttons Step 2. Press thumbs on buttons releasing center assembly Step 3. Rest assembly at 90 degrees Wireway access in seconds without removing lamps or use of any tools! DIMENSIONS* T5L-254 END VIEW T5L-354 END VIEW T5L-454 END VIEW Length Width Height T5L-AL/CRS-254 46.94" 9.90" 3.10" T5L-AL/CRS-354 46.94" 9.90" 3.10" T5L-AL/CRS-454 46.94" 12.93" INSTALLATION DIAGRAM 46.94 44.94 1.00 2.51 3.00 23.47 *Dimensions are subject to change without notice. Consult factory for details


ORDERING GUID



NAILD



BRINGING YOU OUT OF THE DARK AGES!



est Birchwood Avenue Nesa, AZ 85210 L 480.733.6594 480.733.6596 www.aeilighting.com

Fixture Type . Project Name -

Catalog # -Quantity _