

T5 VT4X 354 454 554 654

VT4X Energy Saving High-Performance Weatherproof Enclosures

For Food Processing, Commercial Kitchens, Parking Garages, Car Washes & More

3-, 4-, 5- & 6-Lamp
T5HO Vaportight Fixtures
for Extreme Weather, Sanitized &
High-Ambient Environments



FEATURES & BENEFITS

- T5HO Lamps** - AEI's vaportight, gasketed VT4X enclosure fixtures come in 54-Watt 3-, 4-, 5- and 6-lamp cross sections. The T8 VT4X Series, with T8 lamps, is also available. These fixtures are injection molded for maximum strength in harsh environments for use primarily to provide a degree of protection against corrosion, windblown dust and rain, splashing water, hose-directed water, temporary immersions in water and damage from external ice formation.
- Tool-Free Access** - AEI's vaportight VT4X series features Tool-Free removal of the lens and gear tray for easy wireway access in seconds.



SPECIFICATIONS

HOUSING: - The VT4X is designed specifically for T5 & T8 lamps and comes fully assembled. The housing is weather-resistant for damp or wet locations and is watertight for optimal performance and durability. The VT4X geartray is high-reflective, pre-painted CRS formed at perimeters w/stiffeners for rigidity.

REFLECTIVE: White ballast cover standard. Highly specular MIRO 4 reflectors optional. Consult factory for more details on reflective options.

LENSES: Injection molded polycarbonate diffusers with lineal prisms standard. Damage resistance is ideal for parking garages. Consult AEI factory for other lens options.

MOUNTING/HARDWARE: One-piece stainless steel latches standard. Standard fixture is sold with mounting brackets. Stainless steel mounting brackets are optional. Stainless steel hardware recommended for high pressure-wash environments.

LISTING: The T5 VT4X is NSF & NEMA 4X Rated. Also IP67 Certified, RoHS Compliant & UL Listed for Damp/Wet Locations.

VT4X VAPORTIGHT FIXTURES

NSF NSF Tested & Certified For Food Processing Areas

UL UL-Approved Wet Location Luminaire

NEMA 4X NEMA-Rated Fixture

IP67 CERTIFIED Totally Protected Against Dust & Temporary Immersions

RoHS COMPLIANT Components are compliant with RoHS directives & levels



EASY ACCESS
No Tools Needed

INJECTION MOLDED
For Maximum Strength & Precise Detail

VAPOR TIGHT
All Weather, Extreme Environment Fixture


T5 or T8 LAMPS
Available In A Variety of Lamp Options

DIMENSIONS



	Length	Width	Height
T5 VT4X 3-, 4-Lamp	51"	14.5"	6"
T5 VT4X 5-, 6-Lamp	51"	14.5"	6"

*For custom applications or questions about the VT4X Series please consult the AEI factory.



The T5 VT4X has stainless steel hardware for maximum durability and twelve (12) latches per unit for positive lens retention. There are four geartray options. Integral pin hinges provide for hinging or latching from either side.

*Dimensions are subject to change without notice. Consult factory for details.

ORDERING GUIDE



Fixture Model	# Of Lamps Wattage	Lens	Voltage	Lamp Color	Options	Mounting
T5 VT4X						

CONSULT
AEILighting.com
for
Photometric Information
On This
Fixture

MODEL T5 VT4X=15HO	# OF LAMPS 3=3 Lamp 4=4 Lamps 5=5 Lamps 6=6 Lamps WATTAGE 54=54 Watts <i>Consult Factory When Application</i>	LENS PC=Polycarbonate AC=Impact Resistant Acrylic	VOLTAGE 12=120V 97=97.7V 34=34.7V 48=48.0V UNI=Universal UNIP0=90C Universal	LAMP COLOR 30=3000K 35=3500K 41=4100K 50=5000K 65=6500K <i>Leave Blank If No Lamps</i> <i>800 Series Standard, Add 77 in front of color for 700 Series applications</i>	SENSORS OC1=Alise Sensor OC3=360 Degree Sensor OCLT=360 Degree Low Temp Sensor <i>Consult Factory For More Options</i> CORDS / PLUGS X'C=Length + Cord Only X'CX=Length/Cord + Style/Plug <i>Consult Factory For More Options</i> BALLASTS EMXXXX=Emergency Ballast/Lumens DIM=Dimming Ballast <i>Consult Factory For Ballast Options</i> HOUSING/REFLECTORS M4=MIRO 4 Reflector	OTHER CTD=Cooled Lamps, TG=Tube Guards CST=Custom <i>Consult Factory For Custom Applications and Ordering Number</i>	Mounting VH=V-Hook HK=3/4" Hook GPLX=Grippler + Style (L,S,T,Y) <i>Consult Options Guidelines For Grippler Details</i> HUB=3/4" Hub X'ST=Length + Galvanized Stem SB=3/4" Slide Box Assembly Hub and Stem Optional SP=3/4" Single Point Bracket Hub and Stem Optional
------------------------------	---	--	--	--	---	--	---

AEI LIGHTING INC.
1113 West Birchwood Avenue
Mesa, AZ 85210
TEL 480.733.6594
FAX 480.733.6596
WEB www.aeilighting.com

Project Name _____ Fixture Type _____

Catalog # _____ Quantity _____

ADVANCED ENERGY IDEAS, INC.

T5 VT4X 354 454 554 654