




## 524L

Efficient, reliable work mate for various trimming as well as cutting. The trimmer is easy to operate, maintain and service. The patented X-Torq® engine gives you more power and less fuel consumption and exhaust emissions compared to a conventional engine.



**INTUITIVE CONTROLS**  
The choke and purge are easy to reach and understand.



**AUTO RETURN STOP SWITCH**  
Stop switch automatically resets to the ON position for trouble-free starting.



**X-TORQ® ENGINE**  
The X-Torq® engine design reduces harmful exhaust emissions by up to 75% and increases fuel efficiency by up to 20%.



**EASY STARTING**  
Air purge for very easy starting.

## Features

- Easy to use trimmerhead
- Chromium cylinder bore for extended product life
- Easy to service and maintain starter
- Heavy duty bevel gear
- Efficient air filter
- Adjustable harness hook eyelet
- Tap 'N Go™ trimmer head

## Technical data

Cylinder displacement	1.55 cu.inch / 25.4 cm <sup>3</sup>
Power output	1.27 hp / 0.95 kW
Maximum power speed	8500 rpm
Fuel tank volume	17.25 fl oz / 0.51 lit
Fuel consumption	600 g/kWh
Idling speed	3000 rpm
Spark plug	NGK BPMR8Y
Electrode gap	0.03" / 0.65 mm
Torque, max.	1.2 Nm / 6000 rpm
Clutch engagement speed	4000 rpm (± 120 rpm)
Lubricant type	Husqvarna 2 stroke or equiv. at 50:1
Maximum rpm output shaft	6500 rpm
Equivalent vibration level (ahv, eq) left / right handle	5/3.8 m/s <sup>2</sup>
Sound pressure level at operators ear	98 dB(A)
Sound power level, guaranteed (LWA)	114 dB(A)
Gear ratio	13:19
Drive gear angle	30°
Weight (excl. cutting equipment)	9.7 lbs / 4.4 kg
Tube length	58.39 inch / 1483 mm
Tube diameter	0.94" / 24 mm

### ARTICLES

967 21 05-01	AU/NZ/Asia, T35 + Grass 255-4	\$ 579.00
--------------	-------------------------------	-----------

