

# STATICO

*Global Supplier of Static Control & Cleanroom Products*

*541 Taylor Way, #1. San Carlos, CA 94070. USA. [www.statico.com](http://www.statico.com)*

*Tel.: (650) 592-4733. 1-800-261-4149. Fax: 650-508-0761 [sales@statico.com](mailto:sales@statico.com)*

---

## *Product Specifications*

### *S1506*

## *Anti-Fatigue Static Dissipative Matting*



## Description

S1506 is static dissipative Vinyl matting ideal for areas that requires employees to work on standing position for long hours. It helps to reduce the fatigue, while providing a static free work surface to discharge static build up. Standard roll sizes are 2'x60'; 3'x60' & 4'x60'. Also available in custom sizes on request. This product meets and exceeds ANSI/ESD S20.20-2014.

## Specifications<sup>(1)</sup>

<b>Colors</b>	<b>Gray, Brown</b>
<b>Emboss Patterns</b>	<b>Pebble Emboss</b>
<b>Gauge</b>	<b>0.375" ± 10% (3/8" or 375 mils)</b>
<b>Weight</b>	<b>86 oz/yd<sup>2</sup> nominal</b>
<b>Density</b>	<b>19 lb/ft<sup>3</sup> nominal</b>
<b>Tensile (ASTM D412)</b>	<b>70 lb/in<sup>2</sup></b>
<b>Elongation (ASTM D412)</b>	<b>60%</b>
<b>Tear (ASTM D1004)</b>	<b>15 lb/in</b>
<b>Durometer (ASTM D2240-75)</b>	<b>60 ± 5, Shore 00</b>
<b>Resistivity (ESD S4.1&amp; 4.2)</b>	
<b>R<sub>TT</sub></b>	<b>10<sup>9</sup>-10<sup>10</sup></b>
<b>R<sub>TG</sub></b>	<b>10<sup>9</sup>-10<sup>10</sup></b>
<b>Decay Time (EIA 541)</b>	<b>&lt;2.0 Seconds</b>
<b>Suggested Service Temperature <sup>(2)</sup></b>	<b>-20° F to +160° F</b>

<sup>(1)</sup> Specifications are subject to change at any time for a variety of reasons. If you have any questions, please call for the latest update.

<sup>(2)</sup> This suggested range represents the general temperature range for most flexible vinyl products.

*Due to the variety of possible end-uses, it is ultimately the responsibility of the customer to determine a product's suitability for a Particular application.*