

# STATICO

*Global Static Control & Cleanroom Products*  
541 Taylor Way, #1. San Carlos, CA 94070. USA. [www.statico.com](http://www.statico.com)  
Tel.: (650) 592-4733. 1-800-261-4149. Fax: 650-508-0761. [sales@statico.com](mailto:sales@statico.com)

---

## *Product Specifications*

### *S6000HT Series*

### *Anti Static High Temperature Tape*



### *Description*

The S6000HT Series is an anti static tape, made of Polyester film, coated with a surface conductive adhesive. This tape is used for masking of printed circuit boards during conformal coating, amongst other applications. It leaves no adhesive residue after removal.

### *Specifications*

Supporting Base	Polyester Film
Adhesive	Synthetic Conductive Resin
Base Thickness	1.00 mil (0.025 mm)
Total Thickness	2.2 mill (0.055 mm)
Tensile Strength	23 lbs./inch (40 N/cm)

Elongation	80-120%
Electrical Resistance (Adhesive)	50000-100000 ohms/cm.
Temperature Resistance	Up to 130° C
Adhesive Strength	27 OZ/inch (3.0 N/CM)
Color	Gray
Core Type	Plastic
Core Size	3"
Standard Roll Width*	1/4", 1/2", 3/4", 1" & 2" (6, 12, 18, 24 & 48mm )
Standard Roll Length	72 Yards

\* Other widths available upon request.

### **NOTE**

STATEMENTS, TECHNICAL INFORMATION AND RECOMMENDATIONS CONTAINED HEREIN ARE BASED ON TESTS WE BELIEVE TO BE RELIABLE BUT THEY ARE NOT TO BE CONSTRUED IN ANY MANNER AS WARRANTIES EXPRESSED OR IMPLIED. THE USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT FOR HIS INTENDED USE AND USER ASSUMES ALL RISK AND LIABILITY WHATSOEVER IN CONNECTION THEREWITH.