

Intec-G2® Series



POWER & CONTROL



EXPERIENCE & QUALITY



TECHNOLOGY & INNOVATION



A GMM Group Company



Techjet Upgrade Option - Linear Scale Feedback

ACCURACY WITH LINEAR SCALE FEEDBACK 0,05 mm/m - 0,002"
REPEATAB. WITH LINEAR SCALE FEEDBACK ± 0,025 mm - 0,001"

TECHNICAL DATA

| MODULE | i613-G2 |
|---|--|
| MACHINE SIZE (L x W x H) Does not include pumps or control cabinet | 5200 x 2700 x 2300 mm 205" x 106" x 91" |
| MACHINE WEIGHT | 3600 kg - 7950 lb |
| MACHINE WEIGHT (with water) | 8100 kg - 17860 lb |
| CUTTING TABLE DIMENSION | 1930 x 3870 mm 76" x 152,3" |
| CUTTING AREA (without PAC60) | 1700 x 3700 mm 67" x 145,6" |
| BEVEL CUTTING AREA (with PAC60) | 1700 x 3700 mm 67" x 145,6" |
| CUTTING AREA MAXIMIZED (with PAC60) | 1700 x 3700 mm 67" x 145,6" |
| ACCURACY OF MOTION | 0,15 mm/m - 0,006" |
| REPEATABILITY OF MOTION | ± 0,05 mm - 0,002" |
| MAX. AIR SPEED | 17,5 m/min - 700 in/min |
| MAX. CUTTING SPEED | 17,5 m/min - 700 in/min |
| MAX. MATERIAL THICKNESS (with PAC60) | 130 mm - 5" (130 mm - 5") |

IMPORTANT NOTICE: the technical data is not binding and may be changed by Techni Waterjet without prior notice. All the above accuracy tolerances are correct at the calibration temperature of 20° ± 1° C.


STANDARD FEATURES

REMOTE CONTROL PENDANT



The MPG allows to manually wind forward or backward through a cutting path. This enables the operator to find the exact point along a cutting path from which to re-start cutting after a stoppage, or to accurately locate a pre-cut part.


BREAK AWAY HEAD



When the cutting head inadvertently crashes into a clamp or fixture, or hits the edge of a work piece or an upturned part, the Break Away Head will detect the crash and automatically stop the machine.

Not available with PAC60.

TECH-SENSE



Tech-Sense Monitoring System provides the ability to run a night shift without the need for an attending operator. Should the cutting be disrupted, e.g. blocked nozzle, the machine will pause the program and send a text message to your cell phone.

WATER RAISE AND LOWER



Automatic water Raise/Lower at the push of a button for Submerged Cutting; our tanks include air-tight welds of an air chamber which uses regular shop air pressure.

SERVO Z AXIS



Programmable Z axis with auto height position recall, laser terrain mapping and edge location optics.

HIGH-PRESSURE GAUGE



The HP gauge displays the pressure on the high-pressure water line. This allows the operator to see the actual pressure supplied to the cutting head and assists in troubleshooting.

ELECTRIC SERVO PUMP - Patented

Quantum NXT™

The Quantum NXT™ pump incorporates core "direct servo" technology that was first applied by NASA for the Space Shuttle Program.



VP 15/52

MAX OUTPUT PRESSURE 3585 bar (52,000 psi)
MAX OUTPUT VOLUME 1.9 l/min (0.5 gpm)
Output Volume Based on 480 VAC Electrical Supply

BENEFITS

- 60% more efficient than hydraulic intensifier
- Designed for quick seal service
- Virtually silent with noise level of 70 dbA



ESP 37/66

MAX OUTPUT PRESSURE 4550 bar (66,000 psi)
MAX OUTPUT VOLUME 3.8 l/min (1.0 gpm)
Output Volume Based on 480 VAC Electrical Supply

PAC60 - Patented

The PAC 60™ operating software incorporates the True Cut® algorithms data base, developed to determine the predicted taper at a given surface finish. This taper is then compensated for when cutting the part, anywhere from 0 to 60 degrees, giving you "Precision Angle Control" of any part that can be produced on an X-Y abrasive waterjet cutting machine.



- Cutting parts with a true angle up to +/- 60 degrees with continuous rotation.
- Patented Technology to reduce cutting time significantly.
- Complex 5-Axis Programming made easy and quick to learn.
- Surface Scanner to maintain constant distance between nozzle and workpiece when cutting uneven slabs.
- Positioning accuracy to ± 0.1 degrees.
- Multi-pass cutting for edges with different angle.
- Taper cutting automatic compensation.