

# SPEED CRETE BLUE LINE

## RAPID SETTING, CEMENT BASED REPAIR MORTAR FOR UNDERWATER

### DESCRIPTION

SPEED CRETE BLUE LINE is a proprietary formulation of blended portland cements, finely processed select aggregates, and specific chemical additives designed to provide a rapid set, particularly for underwater use. SPEED CRETE BLUE LINE undergoes a chemical "hyper hydration" and produces a very stable, low permeable, cementitious matrix.

### PRIMARY APPLICATIONS

- Underwater and below grade repairs
- Vertical, overhead and horizontal restoration
- Outstanding material for repair of dams, piers, reservoirs, pilings, seawalls, tunnels, sewer pipe and other underwater surfaces

### FEATURES/BENEFITS

- Initial set in 3 to 5 minutes
- Underwater cure
- High strength
- Durable in fresh and salt water
- Placed without forming, at no slump consistency
- Can be "shaved" to desired contour

### TECHNICAL INFORMATION

#### Material Properties at 75°F (24°C)

##### Compressive Strength psi (MPa) ASTM C 109

24 hours .....3,200 (22.1)

7 days .....4,800 (33.1)

28 days .....6,015 (41.5)

##### Set Time Gilmore ASTM C 266

Initial ..... approx. 3 to 5 min

Final ..... approx. 20 min

##### Flexural Strength psi (MPa) ASTM C 348

7 days .....600 (4.1)

28 days .....700 (4.8)

#### Freeze Thaw Durability Factor ASTM C 666

300 cycles .....98.05%

##### Shrinkage ASTM C 157

7 days .....-0.011%

28 days .....-0.060%

##### Scaling Resistance ASTM C 672

25 cycles ..... 0% loss

Chlorides ASTM D 1411 ..... 0.01%

### PACKAGING

SPEED CRETE BLUE LINE is packaged in 50 lb (22.7 kg) poly-lined bags, and 50 lb (22.7 kg) pails.

### SHELF LIFE

1 year in original, unopened package

### COVERAGE/YIELD

Approximately 0.47 ft<sup>3</sup> (0.013 m<sup>3</sup>) when mixed with 5.5 qt (5.2L) of water per 50 lb (22.7 kg) bag

### DIRECTIONS FOR USE

**Surface Preparation:** Concrete surfaces must be structurally sound, free of loose or deteriorated concrete and free of dust, dirt, paint, efflorescence, oil and all other contaminants. Mechanically abrade the surface to achieve a surface profile equal to CSP 6 - 7 in accordance with ICRI Guideline 310.2. Properly clean profiled area. **Priming:** Clean and prime exposed steel above water with DURALPREP AC. Concrete that is and will remain above water throughout the repair should be primed with a spray or brush coat of DURALPREP AC. DURALPREP AC must be allowed to fully dry prior to the application of SPEED CRETE BLUE LINE. Alternately, a Saturated Surface Dry (SSD) concrete surface can be primed with a scrub coat of SPEED CRETE BLUE LINE. The repair must be made before the scrub coat dries out.

UNDERWATER

SPEED CRETE BLUE LINE

Master Format #:  
35 01 00.00



### The Euclid Chemical Company

19218 Redwood Rd. • Cleveland, OH 44110

Phone: [216] 531-9222 • Toll-free: [800] 321-7628 • Fax: [216] 531-9596

www.euclidchemical.com

An **RPM** Company



**Mixing:** SPEED CRETE BLUE LINE will require approximately 5 to 5.5 qt (4.7 to 5.2 L) of potable water per 50 lb (22.7 kg) bag or pail to achieve the proper mix consistency. Pour the measured amount of water into a clean container. Add the measured amount of SPEED CRETE BLUE LINE, and thoroughly mix for no more than 60 seconds to a stiff, no slump, putty-like consistency. Because of fast initial set time, do not mix more than 50 lb (22.7 kg) at a time. Mix small quantities of SPEED CRETE BLUE LINE in a clean pail with a hand trowel.

**Application:** To ensure complete bond with the entire surface, force the SPEED CRETE BLUE LINE firmly into the Saturated Surface Dry area by hand or with a trowel. Underwater applications may be smoothed or finished by hand. **For out-of-water applications:** Slightly overfill the patch, and following initial set, shave the material to conform to the contour of the surrounding surface. Always shave SPEED CRETE BLUE LINE toward the common bonding edge between the patching material and the existing surface. Cure the material using standard curing practices. For additional information, contact your local Euclid Chemical representative.

## CLEAN-UP

Clean application tools and mixing equipment with water immediately following use. Hardened SPEED CRETE BLUE LINE is difficult to remove.

## PRECAUTIONS/LIMITATIONS

- Store material undercover and away from all moisture.
- Mix no more than 60 seconds.
- Use only potable water with SPEED CRETE BLUE LINE.
- Mix to a stiff, putty-like, no slump consistency.
- Do not re-temper or add sand to SPEED CRETE BLUE LINE.
- Minimum application 3/4 in. (19 mm), maximum application is 3 in. (7.62 cm) per lift.
- Do not overwork or overtrowel the material.
- Do not featheredge SPEED CRETE BLUE LINE.
- Clean mixing equipment between batches.
- In all cases, consult the Material Safety Data Sheet before use.

Rev. 03.13

**WARRANTY:** The Euclid Chemical Company ("Euclid") solely and expressly warrants that its products shall be free from defects in materials and workmanship for one (1) year from the date of purchase. Unless authorized in writing by an officer of Euclid, no other representations or statements made by Euclid or its representatives, in writing or orally, shall alter this warranty. EUCLID MAKES NO WARRANTIES, IMPLIED OR OTHERWISE, AS TO THE MERCHANTABILITY OR FITNESS FOR ORDINARY OR PARTICULAR PURPOSES OF ITS PRODUCTS AND EXCLUDES THE SAME. If any Euclid product fails to conform with this warranty, Euclid will replace the product at no cost to Buyer. Replacement of any product shall be the sole and exclusive remedy available and buyer shall have no claim for incidental or consequential damages. Any warranty claim must be made within one (1) year from the date of the claimed breach. Euclid does not authorize anyone on its behalf to make any written or oral statements which in any way alter Euclid's installation information or instructions in its product literature or on its packaging labels. Any installation of Euclid products which fails to conform with such installation information or instructions shall void this warranty. Product demonstrations, if any, are done for illustrative purposes only and do not constitute a warranty or warranty alteration of any kind. Buyer shall be solely responsible for determining the suitability of Euclid's products for the Buyer's intended purposes.