



The Siva Atom Installation

Thanks for buying the Siva Atom! First, if you are not comfortable removing your bicycle wheel or working with your bicycle, please see your local bike shop or technician for help. Siva Cycle is not responsible for improper installation. Please visit the following website for more detailed installation instructions:

www.sivacycle.com/installation



Completely remove quick release or fastening nut. Be sure to loosen rear brake. NOT for use with disc, drum, or coaster brakes! Place connection hardware aside.



Remove wheel 3-5 inches from frame. No need to completely remove wheel.



Place Siva Atom over wheel axle, pressing silicon spoke drive firmly against spokes.



Replace wheel into frame, replace quick release skewer or fastening nut connection hardware, and begin to tighten, about 80%.



Rotate the Siva Atom next frame as pictured or as close as possible. **Finish tightening axel connection!**



Run USB cord up frame. Attach USB cord with three velcro straps provided.



Secure USB plug to seat post or top tube. Wrap excess cord on underside of USB plug.



Insure USB plug is securely fastened to the seat post or tube by lightly tugging.



Plug in USB cord to check USB plug installation is correct. The USB plug should stretch but not move.



To remove and replace battery pack, simply slide . Be sure to fully replace battery for recharging.



Battery may be recharged from wall outlet with micro-usb in addition to directly from the Siva Atom.

Before you ride:

- Check wheel is securely attached to bicycle
- Check brakes are reconnected before you ride
- Check USB cord is secured with velcro straps
- Check USB plug is securely attached to seat post or top tube
- If you are not confident you correctly installed the Siva Atom, see your local bike professional

If you have any questions, see www.sivacycle.com/installation or email us at info@sivacycle.com.

**Ride your bike. Charge your device.
Create your moment.**