

Advanced Walk-Through Metal Detector VTS-MD-WT-A33

Specifications	
External dimensions	2240 × 670 × 850mm
Vertical channel size	2000 × 700mm
Packing size	2280 × 700 × 290mm
NW	67KG
GW	75KG
Working voltage	AC90V~240V 50/60Hz
Power	12W
Working frequency	1-100
Working environment	-20°~65°C
Installation environment	(W) 100cm × (L) 200cm (no metal in this range)
Highest standard	Metal size≥6g
Protection	IP55
Warranty	2 Years

Technical Parameters	
Electrical reference EN60950 safety standards	√
Radiation standards reference EN50081-1	√
Anti-interference standard reference EN50082-1	√
Strictly enforced Walk Through Metal Detector National Standard(GB15210-2003)	√
ISO9001:2008 certificate	√
OHSAS18001 health certificate	√
ISO14001 environment certificate	√
EU CE FCC ROHS certificates	√

Part Numbers	
MD-WT-A33	Advanced Walk-Thru Metal Detector, 33 detection zones, LCD Touch screen, Real time Monitoring

*The latest product information / specification can be found at www.venturatacticalsystems.com



Key Features

- 33 detection zones
- 7 Inch HDMI LCD touch screen
- Mobile connection technology: APP remote control (optional)
- IP55 protection (waterproof)
- Auto Self calibration upon power up
- Self diagnostic upon power down
- Auto Start-stop technology with infrared devices
- Adjustable audible alarm
- Adjustable working frequency (auto or manual)
- 100 working frequencies
- 100 security levels
- Detection sensitivity of each zone: From 0 to 355 level
- Multi-alarm sounds to choose-to fit different applications
- Counter: Record the pass and alarm numbers
- Real-time information query function.
- Intelligent Standby
- Detection speed of 60 people per minute

Advanced Walk-Through Metal Detector VTS-MD-WT-A33

7-inch LCD capacitive touch screen



Easy install, high-strength plastic beam (customizable length)



Aviation Plugs



Technical Standard

Exclude appointed metal on one body like the belt, bra, etc.	√
7-inch LCD capacitive touch screen	√
Touch-screen operation	√
Mobile APP remote control	Optional
Multiple networking interfaces	√
External control alarm device port	√
Secondary development port/upgrade port	√
Count the number of pass	√
Count the number of alarm	√
Query in/out record	Optional
Dual password protection	√
Multi zone detection, multi alarm	√
Smart Partition	√
Smart Partition alarm indicator	√
Double sides super brightness SMD LED	√

100 working frequency	√
Alarm quiet mode	√
Adjust the alarm sound	√
Multiple alarm sounds	Optional
Front or rear single side alarm light	Optional
Front sides alarm indicate lights	√
Four sides led lights/optional	√
Sensitivity of each zone can be adjusted	√
Adjust sensitivity: 0~355	√
Security level: 1~100	√
33 detection zones	√
Built-in 72 applications	√
Back-up battery continues work for 2h/optional	Optional
Back-up battery continues work for 8h/optional	Optional
Restore factory settings	√



Body Temperature Measurement



Video Recording



Intercom System



Face Recognition