

Baggage Scanner VTS-XR-0500D



KEY FEATURES

- + 650mm(W) × 500mm(H) tunnel size
- + HD image enhancement
- + Image penetration enhancement
- + Rejection of organics

BASIC PARAMETERS

Tunnel size	25.5"(W) × 19.7"(H) / 650mm(W) × 500mm(H)
Conveyor speed	0.72ft/s [0.22m/s]
Conveyor maximum load	220.5lbs [100kg]
Pass rate	700 piece/hour
Metal wire resolution	side view, typical 40AWG / Ø0.0787mm top view, typical 40AWG / Ø0.0787mm
Penetration through steel plate	side view, typical 40mm / top view, typical 40mm
Dose per inspection	typical 4.4µGy/h
X-ray leakage	typical 1.5µGy/h at 2" [5cm] from the machine
Film safety	ISO1600 Film
Food medicine and film	x-ray exposure has no adverse effects
Operating system	Windows

X-RAY GENERATOR

Tube current (adjustable)	0.4 to 1.2mA
Tube voltage (adjustable)	160kV
Beam direction	top, side, angle, 80 degree
Generator quantity	two (double generator)
Cooling/duty cycle	oil cooling/100%

IMAGE PROCESSING

Ray sensor	photodiode array detector (double energy)
Image display	two 24" LCD, high resolution color
Image maximum resolution	1920×1080 pixels
Image storage	60,000 images
Image processing	24bit for processing real time; edge enhancement, straightening, returning, retrieval
Image options	high penetration, low penetration, magnifier, brightening/darkening
Magnifier	1 to 64 times (whole screen continuous observation)
Multi color display for organic energy	orange for organic, blue for inorganic, green for mixture
High energy / low energy	display key
Dangerous goods aided detection	yes (weapons, drugs, explosives)

ELECTRICAL

Operating voltage	110Vac/220Vac (±10%) (specify at time of order)
Power consumption	1kW (max) / 800W (nominal)

ENVIRONMENTAL

Operating temperature	32°F to 114°F [0°C to 45°C]
Storage temperature	-4°F to 140°F [-20°C to 60°C]
Operating humidity	20% to 95% (non-condensing)
Storage humidity	20% to 95% (non-condensing)

CONNECTION

Cable length	15' [5m]
Cable type	USB extension (x2) / monitor power cable monitor VGA cable / security keyboard cable

X-RAY PHYSICAL CHARACTERISTICS

Length	97" [2456mm] - including IN/OUT conveyor belts 66.5" [1690mm] - excluding IN/OUT conveyor belts
Width	53" [1348mm]
Height	52.5" [1331mm]
Conveyor belt height	26.25" [665.5mm]
Weight	1653.5lbs [750kg]

CONSOLE PHYSICAL CHARACTERISTICS

Controller cabinet	dual cabinet (two monitors)
Controller cabinet size	39.37"(W) × 29.5"(D) × 48"(H) 100cm(W) × 75cm(D) × 122cm(H)
Controller cabinet weight	147.7lbs [67kg]

GENERAL

Controls	x-ray unit emergency push button controller keyboard with emergency push button mouse and keyboard
Visual display	green LED - device on red LED - x-ray in-use / calibrating amber LED - alarm
System noise	60 dB
Communication	ethernet

PART NUMBERS

VTS-XR-0500D	x-ray machine with 650×500 tunnel size, Windows operating system, double energy
--------------	---